

Package ‘RApiDatetime’

January 19, 2026

Type Package

Title R API for 'Date' and 'Datetime'

Version 0.0.11

Date 2026-01-19

Description Access to the C-level R date and 'datetime' code is provided for C-level API use by other packages via registration of native functions. Client packages simply include a single header 'RApiDatetime.h' provided by this package, and also 'import' it. The R Core group is the original author of the code made available with slight modifications by this package.

URL <https://github.com/eddelbuettel/rapidatetime>,
<https://dirk.eddelbuettel.com/code/rapidatetime.html>

BugReports <https://github.com/eddelbuettel/rapidatetime/issues>

License GPL (>= 2)

RoxygenNote 6.0.1

OS_type unix

NeedsCompilation yes

Author Dirk Eddelbuettel [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-6419-907X>>),
R Core [aut] (Included date / datetime code)

Maintainer Dirk Eddelbuettel <edd@debian.org>

Repository CRAN

Date/Publication 2026-01-19 14:50:07 UTC

Contents

RApiDatetime-package	2
asDatePOSIXct	2
rapistrptime	3
Index	5

RApiDatetime-package *R API for 'Date' and 'Datetime'*

Description

Access to the C-level R date and 'datetime' code is provided for C-level API use by other packages via registration of native functions. Client packages simply include a single header 'RApiDatetime.h' provided by this package, and also 'import' it. The R Core group is the original author of the code made available with slight modifications by this package.

Package Content

Index of help topics:

RApiDatetime-package	R API for 'Date' and 'Datetime'
asDatePOSIXct	Conversion from POSIXct to Date
rapistrptime	R Wrappers for 'strptime', 'asPOSIXlt' etc

Maintainer

Dirk Eddelbuettel <edd@debian.org>

Author(s)

Dirk Eddelbuettel [aut, cre] (ORCID: <<https://orcid.org/0000-0001-6419-907X>>), R Core [aut] (Included date / datetime code)

asDatePOSIXct *Conversion from POSIXct to Date*

Description

Conversion from POSIXct to Date

Usage

```
asDatePOSIXct(x, tz = "")
```

Arguments

x	A POSIXct vector
tz	An optional timezone string

Details

This function provides a direct conversion from POSIXct to Date. As of R-3.5.1, conversion from POSIXct to Date creates an intermediate POSIXlt object. This intermediate POSIXlt object uses a non-trivial amount of memory. The direct conversion is more memory efficient, and therefore approximately twice as fast as the current solution in base R.

Value

A vector of Date objects

Author(s)

Joshua Ulrich

Examples

```
p <- .POSIXct(1540181413, "America/Chicago")
as.Date(p)                # Using UTC timezone
as.Date(p, "America/Chicago") # Using local timezone
asDatePOSIXct(p)          # Direct, using local timezone
```

rapistrptime

R Wrappers for strptime, asPOSIXlt etc

Description

Wrappers for C-level strptime etc functions

Usage

```
rapistrptime(x, fmt, tz = "")

rapiAsPOSIXlt(x, tz = "")

rapiAsPOSIXct(x, tz = "")

rapiFormatPOSIXlt(x, fmt, usetz = FALSE)

rapiPOSIXlt2D(x)

rapiD2POSIXlt(x)
```

Arguments

x	Vector with one or character elements to be parsed
fmt	The format string, see <code>help("strptime")</code> for details.
tz	An optional timezone string
usetz	An optional logical variable selecting use of the timezone.

Details

These functions provide (additional) entry points from R to the C-level function of the R API. They are provided here mainly for testing (the C level access) as R itself exposes the function

Value

A vector with POSIXlt datetime objects

Author(s)

Dirk Eddelbuettel

Examples

```
op <- options(digits.secs=6)
x <- rapistrptime("2017-01-02 03:04:05.678", "%Y-%m-%d %H:%M:%OS")
format(x)
rapiAsPOSIXlt(as.POSIXct(x))
rapiAsPOSIXct(x)
rapiFormatPOSIXlt(x, "%Y-%b-%d %H:%M:%OS")
options(op)
rapiPOSIXlt2D(x)
rapiD2POSIXlt(as.Date("2017-01-02"))
```

Index

* **package**

RApiDatetime-package, [2](#)

asDatePOSIXct, [2](#)

rapiasPOSIXct (rapistrptime), [3](#)

rapiasPOSIXlt (rapistrptime), [3](#)

rapid2POSIXlt (rapistrptime), [3](#)

RApiDatetime (RApiDatetime-package), [2](#)

RApiDatetime-package, [2](#)

rapiformatPOSIXlt (rapistrptime), [3](#)

rapiposixlt2D (rapistrptime), [3](#)

rapistrptime, [3](#)