

Package ‘bamm’

February 3, 2026

Type Package

Title Species Distribution Models as a Function of Biotic, Abiotic and Movement Factors (BAM)

Version 0.6.0

Maintainer Luis Osorio-Olvera <luismurao@gmail.com>

Description Species Distribution Modeling (SDM) is a practical methodology that aims to estimate the area of distribution of a species. However, most of the work has focused on estimating static expressions of the correlation between environmental variables. The outputs of correlative species distribution models can be interpreted as maps of the suitable environment for a species but not generally as maps of its actual distribution. Soberón and Peterson (2005) <doi:10.17161/bi.v2i0.4> presented the BAM scheme, a heuristic framework that states that the occupied area of a species occurs on sites that have been accessible through dispersal (M) and have both favorable biotic (B) and abiotic conditions (A). The 'bamm' package implements classes and functions to operate on each element of the BAM and by using a cellular automata model where the occupied area of a species at time t is estimated by the multiplication of three binary matrices: one matrix represents movements (M), another abiotic -niche-tolerances (A), and a third, biotic interactions (B). The theoretical background of the package can be found in Soberón and Osorio-Olvera (2023) <doi:10.1111/jbi.14587>.

License GPL (>= 3)

URL <https://luismurao.github.io/bamm/>

BugReports <https://github.com/luismurao/bamm/issues>

Depends R (>= 4.1.0)

Imports animation (>= 2.3), crosstalk, dplyr (>= 0.8.0), furrr (>= 0.1.0), future (>= 1.18.0), graphics, grDevices, igraph (>= 1.2), leaflet (>= 2.0), magrittr (>= 1.2), Matrix (>= 1.2.14), methods (>= 3.3), plotly, purrr (>= 0.2), raster (>= 3.4-13), Rcpp (>= 0.12.18), Rdpack (>= 0.11.0), RSpectra (>= 0.13.1), sp (>= 1.3.0), exactextractr, stats, utils

Suggests knitr, rmarkdown, spelling, testthat (>= 3.0.0)
LinkingTo Rcpp, RcppArmadillo
VignetteBuilder knitr
RdMacros Rdpack
Config/testthat/edition 3
Encoding UTF-8
NeedsCompilation yes
RoxygenNote 7.3.2
SystemRequirements GDAL (>= 2.2.3): gdal-bin (deb), libgdal-dev (deb)
or gdal-devel (rpm), GEOS (>= 3.4.0), PROJ (>= 4.9.3):
libproj-dev (deb), sqlite3, ImageMagick++: imagemagick (deb),
libmagic-dev (deb), libmagick++-dev (deb) or
ImageMagick-c++-devel (rpm) ImageMagick
(<http://imagemagick.org>) or GraphicsMagick
(<http://www.graphicsmagick.org>) or LyX (<http://www.lyx.org>) for
saveGIF(); (PDF)LaTeX for saveLatex(); SWF Tools
(<http://swftools.org>) for saveSWF(); FFmpeg (<http://ffmpeg.org>)
or avconv (<https://libav.org/avconv.html>) for saveVideo()
Language en-US
Author Luis Osorio-Olvera [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-0701-5398>>),
Jorge Soberón [aut] (ORCID: <<https://orcid.org/0000-0003-2160-4148>>),
Rusby G. Contreras-Díaz [ctb] (ORCID:
<<https://orcid.org/0000-0002-0569-8984>>)
Repository CRAN
Date/Publication 2026-02-03 18:30:02 UTC

Contents

adj_mat	3
bam-class	5
bam_clusters	6
bam_sim	7
bam_ssim	9
bioindex-class	11
bioindex_sparse-class	11
community_sim	12
community_sim-class	14
csd-class	14
csd_estimate	15
csim2pam	16
diversity_range-class	17
diversity_range_analysis	18
eigen_bam	20

g_area-class	21
jaccard	22
leaflet-class	23
model2sparse	23
models2pam	24
null_dispersion_field_distribution	25
occs2sparse	26
pam-class	27
pam2bioindex	28
pam2richness	29
permute_pam	30
plot,diversity_range,ANY-method	31
pol2pam	32
predict,bam-method	34
sdm_sim	37
setA-class	39
setM-class	40
shape2Grid	40
show,setA-method	41
sim2Animation	42
sim2Raster	44
Index	46

adj_mat

adj_mat: Function to compute the adjacency matrix of an area.

Description

Creates an adjacency matrix of an area of interest. This could be the accessible area (M) of a species or any geographic region of interest.

Usage

```
adj_mat(modelsparse, ngbs = 1, eigen_sys = FALSE, which_eigs = 1)
```

Arguments

modelsparse	A setA object returned by the function model2sparse .
ngbs	Numeric. Number of neighbors (see details).
eigen_sys	Logical. If TRUE the eigen analyses of the adjacency matrix will be returned.
which_eigs	Numeric. Which eigen value and eigen vector will be returned.

Details

The model is a raster object of the area where the dispersal process will occur.

The function creates an adjacency matrix where cells are considered connected based on:

- The specified neighborhood size ('ngbs')
- The spatial resolution of the input raster
- Only non-NA cells in the original model

When 'eigen_sys = TRUE', the function performs spectral decomposition using [eigs](#), which is particularly useful for:

- Analyzing network connectivity properties
- Identifying clusters or communities in the landscape
- Modeling dispersal processes using spectral graph theory

The number of neighbors depends on the dispersal abilities of the species and the spatial resolution of the niche model; for example, a species's with big dispersal abilities will move throughout more than 1 km² per day, so the idea is to give an approximate number of moving neighbors (pixels) per unit of time.

Value

Returns an object of class [setM](#) with 7 slots. The first contains the adjacency matrix. A n x n sparse matrix (n=number of non-NA cells of the niche model) where connected cells are represented by 1. The second slot has the adjacency list. It is a list of matrices with four columns (FromRasCell -from cell ID of the raster-, -to cell ID of the raster-, -from non-NA cell-, -to non-NA cell-). Other slots contain information about initial coordinates where dispersal occurs (initial_points), number of cells used to define the neighborhood (ngbs), non-NA coordinates (coordinates), and a matrix of eigen vectors (eigen_vec).

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberón J, Osorio-Olvera L (2023). "A dynamic theory of the area of distribution." *Journal of Biogeography*6, **50**, 1037-1048. doi:10.1111/jbi.14587, <https://onlinelibrary.wiley.com/doi/abs/10.1111/jbi.14587..>

See Also

- [model2sparse](#) for creating the input 'setA' object
- [setM](#) for the output class structure
- [eigs](#) for the eigen decomposition implementation

For more information about see adjacency matrices in the context of the theory of area of distribution (Soberon and Osorio-Olvera, 2022).

Examples

```

x_coord <- c(-106.5699, -111.3737, -113.9332,
             -110.8913, -106.4262, -106.5699)
y_coord <- c(16.62661, 17.72373, 19.87618,
             22.50763, 21.37728, 16.62661)
xy <- cbind(x_coord, y_coord)
p <- sp::Polygon(xy)
ps <- sp::Polygons(list(p),1)
sps <- sp::SpatialPolygons(list(ps))
mx_grid <- bamm::shape2Grid(sps,resolution = 0.25,ones = TRUE)
mx_sparse <- bamm::model2sparse(model=mx_grid, threshold = 0.1)
adj_mx <- bamm::adj_mat(modelsparse=mx_sparse,
                       ngbs=1,eigen_sys=TRUE,which_eigs=1)

print(adj_mx)
mx_grid_eigen <- mx_grid
mx_grid_eigen[mx_sparse@cellIDs] <- adj_mx@eigen_vec
raster::plot(mx_grid_eigen)

```

bam-class

*Class bam digram***Description**

Class bam digram

Value

An object of class bam

Slots

`sdm_sim` A list of sparse vectors representing the area occupied

`palatable_matrices` A list of sparse vectors representing palatable sites.

`sim_steps` Number of simulation steps by the species

Author(s)

Luis Osorio-Olvera & Jorge Soberón

bam_clusters	<i>bam_clusters: Function to estimate the connectivity of suitable areas</i>
--------------	--

Description

Function to estimate the connectivity of suitable areas given an adjacency matrix.

Usage

```
bam_clusters(model, ngbs = 1, set_M = NULL, plot_model = FALSE)
```

Arguments

model	A niche model in raster format or a setA object (see model2sparse).
ngbs	Numeric. Number of neighbors (see details).
set_M	A setM object containing the adjacency matrix of the study area. The default value is set to NULL
plot_model	Logical. Indicates whether to plot the niche model using a leaflet map, connected suitable cells shown in the same color.

Details

The main result of the function is the Connectivity-Suitability-Diagram (CSD). In this diagram connected suitable cells make clusters of pixels. For more details about the CSD see (Soberon and Osorio-Olvera, 2022).

Value

An object of class [csd](#). It contains three slots. 1) connections: a data.frame with three columns where first and the second represent (x and y) centroid coordinates of the niche model and the third column with the cluster ID where they belong. 2) interactive_map: a leaflet map of connected suitable pixels shown in the same color. 3) A RasterLayer of connected suitable pixels.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberón J, Osorio-Olvera L (2023). “A dynamic theory of the area of distribution.” *Journal of Biogeography*6, **50**, 1037-1048. doi:10.1111/jbi.14587, <https://onlinelibrary.wiley.com/doi/abs/10.1111/jbi.14587..>

Examples

```

set.seed(891)
model_path <- system.file("extdata/Lepus_californicus_cont.tif",
                           package = "bamm")
model <- raster::raster(model_path)
model <- model > 0.7
clusterin <- bamm::bam_clusters(model,ngbs=1,plot_model=TRUE)
raster::plot(clusterin@raster_map)

clusterin@interactive_map

```

bam_sim	<i>bam_sim: Simulate dispersal dynamics using the set B of the BAM framework.</i>
---------	---

Description

bam_sim: Simulate dispersal dynamics using the set B of the BAM framework.

Usage

```

bam_sim(
  sp1,
  sp2,
  set_M,
  initial_points,
  periods_toxic,
  periods_suitable,
  nsteps,
  progress_bar = TRUE
)

```

Arguments

sp1	Niche model of the focal species (the one that disperses).
sp2	Niche model of the species with whom sp1 interacts (currently no dispersal dynamics for this species).
set_M	A setM object containing the adjacency matrix for sp1. See adj_mat
initial_points	A sparse vector returned by the function occs2sparse
periods_toxic	Time periods that sps2 takes to develop defense mechanisms (i.e. toxic).
periods_suitable	This is the time that sp2 takes to become non-toxic
nsteps	Number of steps to run the simulation
progress_bar	Show progress bar

Details

The returned object inherits from `setA`, `setM` classes. Details about the dynamic model can be found in Soberon and Osorio-Olvera (2022). The model is cellular automata where the occupied area of a species at time $t + 1$ is estimated by the multiplication of three binary matrices: one matrix represents movements (M), another abiotic -niche- tolerances (A), and a third, biotic interactions (B) (Soberon and Osorio-Olvera, 2022).

$$\mathbf{G}_j(t + 1) = \mathbf{B}_j(t)\mathbf{A}_j(t)\mathbf{M}_j\mathbf{G}_j(t)$$

Value

An object of class bam. The object contains 12 slots of information (see details) from which simulation results are stored in `sdm_sim` object, a list of sparse matrices with results of each simulation step.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberón J, Osorio-Olvera L (2023). “A dynamic theory of the area of distribution.” *Journal of Biogeography*6, **50**, 1037-1048. doi:10.1111/jbi.14587, <https://onlinelibrary.wiley.com/doi/abs/10.1111/jbi.14587..>

Examples

```
# Compute dispersal dynamics of Urania boisduvalii as a function of
# palatable Omphalea
urap <- system.file("extdata/urania_omph/urania_guanahacabibes.tif",
                    package = "bamm")

ura <- raster::raster(urap)
ompp <- system.file("extdata/urania_omph/omphalea_guanahacabibes.tif",
                    package = "bamm")

omp <- raster::raster(ompp)
msparse <- bamm::model2sparse(ura)
init_coordsdf <- data.frame(x=-84.38751, y= 22.02932)
initial_points <- bamm::occs2sparse(modelsparse = msparse,init_coordsdf)
set_M <- bamm::adj_mat(modelsparse = msparse,ngbs = 1)
ura_sim <- bamm::bam_sim(sp1=ura, sp2=omp, set_M=set_M,
                        initial_points=initial_points,
                        periods_toxic=5,
                        periods_suitable=1,
                        nsteps=40)

ura_omp <- bamm::sim2Raster(ura_sim)
raster::plot(ura_omp[[c(1,5,10,15,20,30,35,40)]])

if(requireNamespace("animation")){
  # Animation example
  anp <- tempfile(pattern = "simulation_results_",fileext = ".gif")
  # new_sim <- bamm::sim2Animation(sdm_simul = ura_sim,
```

```
#                               which_steps = seq_len(ura_sim@sim_steps),
#                               fmt = "GIF",
#                               filename = anp)
}
```

bam_ssim	<i>bam_ssim: Simulate dispersal dynamics using the set B of the BAM framework.</i>
----------	--

Description

bam_ssim: Simulate dispersal dynamics using the set B of the BAM framework.

Usage

```
bam_ssim(
  sp1,
  sp2,
  set_M,
  initial_points,
  periods_toxic,
  periods_suitable,
  dispersal_prob = 0.85,
  palatable_matrices = FALSE,
  nsteps,
  progress_bar = TRUE
)
```

Arguments

sp1	Niche model of the focal species (the one that disperses).
sp2	Niche model of the species with whom sp1 interacts (currently no dispersal dynamics for this species).
set_M	A setM object containing the adjacency matrix for sp1. See adj_mat
initial_points	A sparse vector returned by the function occs2sparse
periods_toxic	Time periods that sp2 takes to develop defense mechanisms (i.e. toxic).
periods_suitable	This is the time that sp2 takes to become non-toxic
dispersal_prob	A numeric value indicating the probability to disperse to neighboring cells. This probability is assumed to be binomially distributed
palatable_matrices	Logical. If TRUE palatable matrices for each time will be returned.
nsteps	Number of steps to run the simulation
progress_bar	Show progress bar

Details

The returned object inherits from `setA`, `setM` classes. Details about the dynamic model can be found in Soberon and Osorio-Olvera (2022).

Value

An object of class `bam`. The object contains 12 slots of information (see details) from which simulation results are stored in `sdm_sim` object, a list of sparse matrices with results of each simulation step. Palatable matrices are returned as a list of sparse matrices with information about palatable pixels for each step of the simulation.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberón J, Osorio-Olvera L (2023). "A dynamic theory of the area of distribution." *Journal of Biogeography* 6, **50**, 1037-1048. doi:10.1111/jbi.14587, <https://onlinelibrary.wiley.com/doi/abs/10.1111/jbi.14587..>

Examples

```
urap <- system.file("extdata/urania_omph/urania_guanahacabibes.tif",
                   package = "bamm")
ura <- raster::raster(urap)
ompp <- system.file("extdata/urania_omph/omphalea_guanahacabibes.tif",
                   package = "bamm")
omp <- raster::raster(ompp)
msparse <- bamm::model2sparse(ura)
init_coordsdf <- data.frame(x=-84.38751, y= 22.02932)
initial_points <- bamm::occs2sparse(modelsparse = msparse,init_coordsdf)
set_M <- bamm::adj_mat(modelsparse = msparse,ngbs = 1)
ura_ssim <- bamm::bam_ssim(sp1=ura, sp2=omp, set_M=set_M,
                        dispersal_prob = 0.75,
                        initial_points=initial_points,
                        periods_toxic=5,
                        periods_suitable=1,
                        nsteps=40)
ura_omp <- bamm::sim2Raster(ura_ssim)
raster::plot(ura_omp[[c(1,2,5,10,15,20,30,35,40)]])

if(requireNamespace("animation")){
  # Animation example
  anp <- tempfile(pattern = "simulation_results_",fileext = ".gif")
  #new_sim <- bamm::sim2Animation(sdm_simul = ura_ssim,
  #                               which_steps = seq_len(ura_ssim@sim_steps),
  #                               fmt = "GIF",
  #                               filename = anp)
}
```

bioindex-class	<i>Class</i> bioindex
----------------	-----------------------

Description

Class bioindex

Value

An object of class bioindex

Slots

alpha A matrix with the richness of species per site
 omega A matrix with the range size of every species
 wBeta A numeric value with Whittaker's multiplicative beta index
 laBeta A numeric value with Lande's additive beta index
 leBeta A numeric value with Legendre's beta index
 nestedness A numeric value with Wright and Reeves' nestedness
 dispersion_field A matrix with the set of ranges of all species that occur in at each locality
 richness_field A matrix with the number of shared species in each site

Author(s)

Luis Osorio-Olvera & Jorge Soberón

bioindex_sparse-class	<i>Class</i> bioindex_sparse
-----------------------	------------------------------

Description

Class bioindex_sparse

Value

An object of class bioindex_sparse

Slots

alpha A sparse matrix with the richness of species per site
 omega A sparse matrix with the range size of every species
 wBeta A numeric value with Whittaker's multiplicative beta index
 laBeta A numeric value with Lande's additive beta index
 leBeta A numeric value with Legendre's beta index
 nestedness A numeric value with Wright and Reeves' nestedness
 dispersion_field A sparse matrix with the set of ranges of all species that occur in at each locality
 richness_field A sparse matrix with the number of shared species in each site

Author(s)

Luis Osorio-Olvera & Jorge Soberón

community_sim

community_bam: Community bamm

Description

Estimate community dynamics using the bamm framework

Usage

```
community_sim(
  en_models,
  ngbs_vect,
  init_coords,
  nsteps,
  threshold_vec = NULL,
  stochastic_dispersal = FALSE,
  disp_prop2_suitability = TRUE,
  disper_prop = 0.5,
  rcpp = TRUE
)
```

Arguments

en_models	A stack or directory with the ecological niche models for each species in the community.
ngbs_vect	A vector containing the number of neighbors for each adjacency matrix of each species in the community see adj_mat .
init_coords	A data.frame with 3 columns: sp_name, x and y; x is the longitude and y is the latitude of initial dispersal points

nsteps	Number of iteration steps for the simulation.
threshold_vec	A vector of threshold values used to binarize niche models.
stochastic_dispersal	Logical. If dispersal depends on a probability of visiting neighbor cells (Moore neighborhood).
disp_prop2_suitability	Logical. If probability of dispersal is proportional to the suitability of reachable cells. The proportional
disper_prop	Probability of dispersal to reachable cells.
rcpp	Logical. Use native C++ code to run the model. value must be declared in the parameter 'disper_prop'.

Details

Each element in community_sim is an object of class. For more details about the simulation see [sdm_sim.bam](#).

Value

An object of class community_sim. The object contains simulation results for each species in the community.

Author(s)

Luis Osorio-Olvera & Jorge Soberon

References

Soberón J, Osorio-Olvera L (2023). "A dynamic theory of the area of distribution." *Journal of Biogeography* 6, **50**, 1037-1048. doi:10.1111/jbi.14587, <https://onlinelibrary.wiley.com/doi/abs/10.1111/jbi.14587..>

Examples

```
lagos_path <- system.file("extdata/conejos",
                          package = "bamm")
enm_path <- list.files(lagos_path,
                      pattern = ".tif",
                      full.names = TRUE)[seq(1,10)]
en_models <- raster::stack(enm_path)
ngbs_vect <- sample(1:2,replace = TRUE,
                  size = raster::nlayers(en_models))
init_coords <- read.csv(file.path(lagos_path,
                                "lagos_initit.csv"))[seq(1,10),]

nsteps <- 12
sdm_comm <- bamm::community_sim(en_models = en_models,
                               ngbs_vect = ngbs_vect,
                               init_coords = init_coords,
                               nsteps = nsteps)
```

```
com_pam <- bamm::csim2pam(sdm_comm,which_steps = seq(1,nsteps))
rich_pam <- pam2richness(com_pam,which_steps = c(1,5,10))
raster::plot(rich_pam)
```

community_sim-class	<i>Class community_sim digram</i>
---------------------	-----------------------------------

Description

Class community_sim digram

Value

An object of class community_sim

Slots

community_sim A list of sparse vectors representing the area occupied by the species

Author(s)

Luis Osorio-Olvera & Jorge Soberón

csd-class	<i>Class csd</i>
-----------	------------------

Description

Class csd

Value

An object of class csd

Slots

connections A data.frame with four columns: x, y, clusterID and cluster_size

interactive_map A leaflet map with markers showing the geographical clusters

raster_map A raster map with cluster IDs as values.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

csd_estimate	<i>csd_estimate: Estimate the connectivity suitability and dispersal plot</i>
--------------	---

Description

csd_plot gives an estimate of the number of geographic clusters given a set of dispersal hypothesis and a suitability raster

Usage

```
csd_estimate(model, dispersal_steps = c(2, 4, 8, 16, 32, 64))
```

Arguments

model	A raster model or a setA object representing the suitability model
dispersal_steps	A numeric vector with elements representing the dispersal hypothesis to test.

Details

For more information about the Connectivity-Suitability-Diagram see [bam_clusters](#)

Value

A list of length three. The first element contains the Connectivity- Suitability-Diagram information estimated for each element in the vector of dispersal_steps. The second is tbl_df object with a summary of the number of cluster of each dispersal step and the mean number of connected clusters. The last element is base plot showing the information contained in the tbl_df object.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberón J, Osorio-Olvera L (2023). "A dynamic theory of the area of distribution." *Journal of Biogeography*6, **50**, 1037-1048. doi:10.1111/jbi.14587, <https://onlinelibrary.wiley.com/doi/abs/10.1111/jbi.14587..>

Examples

```
model_path <- system.file("extdata/Lepus_californicus_cont.tif",
                           package = "bamm")
model <- raster::raster(model_path)
model <- model > 0.7
csd_plot <- bamm::csd_estimate(model,
                               dispersal_steps=c(2,4,8))
csd_plot$plot
```

csim2pam	<i>csim2pam: Converts community simulation to a Presence Absence Matrix (PAM)</i>
----------	---

Description

Converts community simulation object into a Presence Absence Matrices (PAM) for a given simulation steps.

Usage

```
csim2pam(community_sim, which_steps, progress_bar = TRUE)
```

Arguments

community_sim	An object of class <code>community_bam</code> .
which_steps	Steps in the simulation object to be converted into a PAM
progress_bar	Show progress bar

Details

For details about the object `community_sim` see `community_sim`

Value

An object of class `pam`; it contains five slots. 1) `pams`: a list of sparse matrices with Presence-Absence information (PAMs). 2) `which_steps`: time steps corresponding to each PAM. 3) `sp_names`: a vector of species names. 4) the grid area used in the simulation. 5) Non NA cell (pixel) IDs.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberón J, Osorio-Olvera L (2023). "A dynamic theory of the area of distribution." *Journal of Biogeography* 6, **50**, 1037-1048. doi:10.1111/jbi.14587, <https://onlinelibrary.wiley.com/doi/abs/10.1111/jbi.14587..>

Examples

```
lagos_path <- system.file("extdata/conejos",
  package = "bamm")
enm_path <- list.files(lagos_path,
  pattern = ".tif",
  full.names = TRUE)[seq(1,10)]
en_models <- raster::stack(enm_path)
ngbs_vect <- sample(1:2,replace = TRUE,
```

```

        size = raster::nlayers(en_models))
init_coords <- read.csv(file.path(lagos_path,
                                "lagos_initit.csv"))[seq(1,10),]
nsteps <- 10
sdm_comm <- bamm::community_sim(en_models = en_models,
                               ngbs_vect = ngbs_vect,
                               init_coords = init_coords,
                               nsteps = nsteps,
                               threshold = 0.1)

pamt10 <- bamm::csim2pam(community_sim = sdm_comm ,
                        which_steps = 10)
pams <- bamm::csim2pam(community_sim = sdm_comm ,
                      which_steps = seq_len(10))
rich_pam <- bamm::pam2richness(pams,which_steps = c(1,5))
print(rich_pam)

```

diversity_range-class *Class diversity_range*

Description

Class `diversity_range`

Value

An object of class `diversity_range`

Slots

`alpha` A column vector with species richness per site
`omega` A column vector with the size of the area of distribution per species.
`alpha_raster` Species richness in raster format.
`dispersion_field` A matrix with the set of ranges of all species that occur in at each locality.
`dispersion_field_raster` Raster object with the observed values of dispersion field.
`diversity_range_raster` Raster object of diversity range.
`diversity_range_colors` Colors to plot endemism levels.
`null_dispersion_field_dist` A matrix with dispersion field null distribution.
`xy_coordinates` A matrix of geographical coordinates
`n_iterations` Number of iterations used to estimate the dispersion field null distribution.
`nsps` Number of species in the PAM.
`nsites` Number of sites in the PAM.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

diversity_range_analysis

range_diversity_analysis: diversity analysis

Description

diversity_range_analysis biodiversity indices related to diversity-range plots

Usage

```
diversity_range_analysis(
  pam,
  xy_mat = NULL,
  lower_interval = 0.05,
  upper_interval = 0.95,
  raster_template = NULL,
  niter = 100,
  return_null_dfield = FALSE,
  randal = "fastball",
  parallel = TRUE,
  n_cores = 2
)
```

Arguments

pam	A Presence-Absence-Matrix of matrix class or sparse matrix.
xy_mat	A two dimensional matrix with longitude and latitude data.
lower_interval	Lower interval.
upper_interval	Upper interval.
raster_template	A raster template.
niter	Number of iterations to obtain the distribution.
return_null_dfield	If TRUE the null distribution of dispersal field will be returned.
randal	Randomization algorithm applied to the PAM. Possible choices "curveball", "fastball" and "indep_swap".
parallel	If TRUE the computations will be performed in parallel.
n_cores	Number of cores for the parallel computation.

Details

For more information about the biodiversity indices see Soberon and Cavner (2015). For detail about the diversity range analysis see Soberon et al. (2022). To plot diversity range results use [plot](#) method for objects of class [diversity_range](#).

For details about randomization algorithms applied to the PAM see [null_dispersion_field_distribution](#).

Value

An object of class `diversity_range`. The main result is the diversity range analysis which shows jointly two indices describing the community composition of every cell in the grid: (1) the relative number of species, and (2) the mean dispersion field (see plot method for `plot` (Soberon et al. 2022)). The contains 12 slots with different measurements of biodiversity such as alpha diversity (species richness in each site or pixel), omega (size of the area of distribution of each species), dispersion field (the standardized size of the area of distribution of all species occurring in each pixel).

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

- Soberón J, Cobos ME, Nuñez-Penichet C (2021). “Visualizing species richness and site similarity from presence-absence matrices.” *Biodiversity Informatics*, **16**(1), 20–27. doi:10.17161/bi.v16i1.14782, <https://journals.ku.edu/jbi/article/view/14782>..
- Soberon J, Caver J (2015). “Indices of Biodiversity Pattern Based on Presence-Absence Matrices: A GIS Implementation.” *Biodiversity Informatics*, **10**, 22–34..

Examples

```
set.seed(111)
pam <- matrix(rbinom(10000,1,0.5),nrow = 100,ncol = 1000)
rdivan <- bamm::diversity_range_analysis(pam=pam,
                                       parallel = FALSE,
                                       niter = 10,
                                       return_null_dfield=TRUE)

bamm::plot(rdivan,plot_type="diversity_range")
# Lagomorphos

lagos_path <- system.file("extdata/conejos",
                          package = "bamm")
enm_path <- list.files(lagos_path,
                      pattern = ".tif",
                      full.names = TRUE)
en_models <- raster::stack(enm_path) >0.01
nonas <- which(!is.na(en_models[[1]]))
xy_mat <- sp::coordinates(en_models[[1]])[ nonas,]
pam <- bamm::models2pam(en_models,sparse=FALSE)

rdivan <- bamm::diversity_range_analysis(pam=pam,
                                       xy_mat=xy_mat,
                                       raster_template = en_models[[1]],
                                       parallel=TRUE,
                                       n_cores=1,
                                       return_null_dfield=TRUE)

bamm::plot(rdivan,plot_type="diversity_range")
bamm::plot(rdivan,plot_type="diversity_range_map")
if(require(plotly) && require(crosstalk)){
```

```
#bamm::plot(rdivan,plot_type="diversity_range_interactive")
}
```

eigen_bam

eigen_bam: Compute the Eigen system of two bam objects

Description

Calculates the Eigen values and Eigen vectors of bam objects

Usage

```
eigen_bam(A = NULL, M = NULL, AM = TRUE, which_eigen = 1, rmap = TRUE)
```

Arguments

A	A bam object of class setA.
M	A bam object of class setM.
AM	A logical value to specify whether to use the product AM or MA. If true the AM will be returned else the product MA will be returned.
which_eigen	An integer representing the which eigen value and eigen vector will be computed.
rmap	Logical. If TRUE the function will return a map of the eigen vector of the product AM.

Details

The eigenvector associated with the dominant eigenvalue of an adjacency matrix provides information about the number of forms in which a cell can be visited from other cells. Details about the eigen analysis in the context of the area of distribution can be found in Soberon and Osorio-Olvera (2022).

Value

A list with four objects. 1) eigen_values (these are indicated in which_eigen parameter of the function), 2) eigen_vectors (the corresponding eigen vectors of each eigen value), 3) Standardized eigen vectors (0 to 1), 4) A RasterLayer depicting the information of the first eigen vector of the system.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberón J, Osorio-Olvera L (2023). “A dynamic theory of the area of distribution.” *Journal of Biogeography* 6, **50**, 1037-1048. doi:10.1111/jbi.14587, <https://onlinelibrary.wiley.com/doi/abs/10.1111/jbi.14587..>

Examples

```
model_path <- system.file("extdata/Lepus_californicus_cont.tif",
  package = "bamm")
model <- raster::raster(model_path)
sparse_mod <- bamm::model2sparse(model = model, 0.75)
plot(sparse_mod@niche_model)
adj_mod <- bamm::adj_mat(sparse_mod, ngbs = 1, eigen_sys = TRUE)
# Product AM
eig_bam_am <- bamm::eigen_bam(A=sparse_mod, M=adj_mod, AM=TRUE)
raster::plot(eig_bam_am$map)
# Product MA
eig_bam_ma <- bamm::eigen_bam(A=sparse_mod, M=adj_mod, AM=FALSE)
raster::plot(eig_bam_ma$map)
```

g_area-class

S4 Class Hierarchy for BAM (Biotic-Abiotic-Movement) Modeling

Description

This documentation describes the S4 class system used in the bamm package for modeling species distributions using the BAM (Biotic-Abiotic-Movement) framework. The classes organize data and results for ecological niche modeling, dispersal simulation, and biodiversity analysis.

The foundational class containing geographic coordinates and optional eigen analysis results for spectral graph methods.

Slots

coordinates A numeric matrix with two columns (x, y) representing geographic coordinates of non-NA cells

eigen_vec Matrix containing eigenvectors from adjacency matrix analysis

eigen_val Numeric vector containing eigenvalues from adjacency matrix analysis

Author(s)

Luis Osorio-Olvera & Jorge Soberón

See Also

[setA-class](#), [setM-class](#)

jaccard

*jaccard: Estimates the Jaccard index for comparing two binary maps***Description**

Estimates the Jaccard index for comparing two binary maps

Usage

```
jaccard(m1, m2)
```

Arguments

m1 A binary raster A or an object of class setA returned by the function [model2sparse](#).
m2 A binary raster A or an object of class setA returned by the function [model2sparse](#).

Details

The Jaccard index is computed as follows

$$J(A, B) = \frac{|A \cap B|}{|A \cup B|} = \frac{|A \cap B|}{|A| + |B| - |A \cap B|}.$$

Value

Returns a data.frame with three values: 1) jaccard (Jaccard index), 2) percentage_m1 (the percentage of m1 that the intersection $|A \cap B|$ represents), and 3) percentage_m2

Author(s)

Luis Osorio-Olvera & Jorge Soberón

Examples

```
m1_path <- system.file("extdata/conejos/Lepus_othus_cont.tif",
                        package = "bamm")
m2_path <- system.file("extdata/conejos/Brachylagus_idahoensis_cont.tif",
                        package = "bamm")
m1 <- raster::raster(m1_path) > 0.01
m2 <- raster::raster(m2_path) > 0.01
jcc <- bamm::jaccard(m1, m2)
print(jcc)
```

leaflet-class	<i>Class leaflet leaflet</i>
---------------	------------------------------

Description

Class leaflet leaflet

Value

An object of class leaflet

Author(s)

Luis Osorio-Olvera & Jorge Soberón

model2sparse	<i>model2sparse: Converts a niche model into a diagonal sparse matrix</i>
--------------	---

Description

model2sparse: Converts a niche model into a diagonal sparse matrix

Usage

```
model2sparse(model, threshold = NULL)
```

Arguments

model	A raster object representing the geographic projection of a niche model.
threshold	A threshold to convert a continuous model into a binary model.

Details

threshold parameter represents the suitability value used to convert continuous model into a binary model.

Value

An object of class [setA](#). The niche model is stored as diagonal sparse matrix (slot sparse_model).

Author(s)

Luis Osorio-Olvera & Jorge Soberón

Examples

```

model_path <- system.file("extdata/Lepus_californicus_cont.tif",
                           package = "bamm")
model <- raster::raster(model_path)

sparse_mod <- bamm::model2sparse(model, threshold=0.75)
print(sparse_mod)
raster::plot(sparse_mod@niche_model)

```

models2pam

*models2pam: Converts binary rasters to a PAM***Description**

Function to convert binary raster models to a Presence Absences Matrix.

Usage

```

models2pam(
  mods_stack,
  return_coords = FALSE,
  sparse = TRUE,
  parallel = FALSE,
  ncores = 2
)

```

Arguments

mods_stack	A raster stack containing binary models of each species in the community.
return_coords	Logical. If TRUE the pam will be returned with coordinates in the first two columns.
sparse	Logical. If TRUE the PAM will be returned as a sparse matrix.
parallel	Logical. If TRUE computations will be done in parallel
ncores	Integer. Number of cores to run the parallel process.

Details

For more information about PAM see Soberon and Cavner (2015).

Value

A presence-absence matrix (PAM).

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberon J, Cavner J (2015). "Indices of Biodiversity Pattern Based on Presence-Absence Matrices: A GIS Implementation." *Biodiversity Informatics*, **10**, 22–34..

Examples

```
lagos_path <- system.file("extdata/conejos",
                          package = "bamm")
enm_path <- list.files(lagos_path,
                      pattern = ".tif",
                      full.names = TRUE)[1:10]
en_models <- raster::stack(enm_path) > 0.01
pam <- bamm::models2pam(en_models,
                       return_coords=TRUE,
                       sparse=FALSE,
                       parallel=FALSE, ncores=1)

head(pam)
```

null_dispersion_field_distribution

null_dispersion_field_distribution: Null distribution of the dispersion field

Description

null_dispersion_field_distribution estimates a random distribution of the dispersion field values.

Usage

```
null_dispersion_field_distribution(
  pam,
  n_iter = 10,
  randal = "fastball",
  parallel = TRUE,
  n_cores = 2
)
```

Arguments

pam	A Presence-Absence-Matrix of matrix class or sparse matrix.
n_iter	Number of iterations to obtain the distribution.
randal	Randomization algorithm applied to the PAM. Possible choices "curveball", "fastball", and "indep_swap".
parallel	If TRUE the computations will be performed in parallel.
n_cores	Number of cores for the parallel computation.

Details

Estimates a random distribution of the dispersion field values. To obtain random values it uses the function `permute_pam` at each step of the iterations. Randomization of the PAM can be performed using the "fastball" (Godard and Neal, 2022) and the "curveball" (Strona et al., 2014), and the independent swap (Kembel et al. 2010) algorithms. The implementation of the "fastball" in C++ is provided in <https://github.com/zpneal/fastball/blob/main/fastball.cpp>

Value

A data matrix of size `nrow(pam) X n_iter` with dispersion field values.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

- Soberon J, Cavner J (2015). "Indices of Biodiversity Pattern Based on Presence-Absence Matrices: A GIS Implementation." *Biodiversity Informatics*, **10**, 22–34.
- Strona G, Nappo D, Boccacci F, Fattorini S, San-Miguel-Ayanz J (2014). "A fast and unbiased procedure to randomize ecological binary matrices with fixed row and column totals." *Nature Communications*, **5**(1), 1–9. ISSN 20411723, doi:10.1038/ncomms5114, <https://www.r-project.org>.
- Godard K, Neal ZP (2022). "fastball: a fast algorithm to randomly sample bipartite graphs with fixed degree sequences." *Journal of Complex Networks*, **10**(6), cnac049. ISSN 2051-1329, doi:10.1093/comnet/cnac049, <https://academic.oup.com/comnet/article-pdf/10/6/cnac049/47758701/cnac049.pdf>.
- Kembel SW, Cowan PD, Helmus MR, Cornwell WK, Morlon H, Ackerly DD, Blomberg SP, Webb CO (2010). "Picante: R tools for integrating phylogenies and ecology." *Bioinformatics*, **26**, 1463–1464.

Examples

```
set.seed(111)
pam <- matrix(rbinom(100,1,0.3),nrow = 10,ncol = 10)
dfield_rand <- bamm::null_dispersion_field_distribution(pam,n_iter=10,
                                                    parallel=FALSE,
                                                    randal="indep_swap",
                                                    n_cores = 2)

head(dfield_rand)
```

occs2sparse

occs2sparse: Converts occurrence data into a sparse matrix object

Description

occs2sparse: Converts occurrence data into a sparse matrix object

Usage

```
occs2sparse(modelsparse, occs)
```

Arguments

modelsparse A setA object returned by the function [model2sparse](#)

occs A matrix or a data.frame containing two columns. The first one is the longitude and the second is the latitude.

Details

Rows of this column vector represent non NA pixels of the niche model.

Value

A sparse vector of zeros (presences) and ones (absences).

Author(s)

Luis Osorio-Olvera & Jorge Soberón

Examples

```
model_path <- system.file("extdata/Lepus_californicus_cont.tif",
                           package = "bamm")
model <- raster::raster(model_path)

sparse_mod <- bamm::model2sparse(model, threshold=0.05)

occs_lep_cal <- data.frame(longitude = c(-115.10417,
                                          -104.90417),
                           latitude = c(29.61846,
                                          29.81846))

occs_sparse <- bamm::occs2sparse(modelsparse = sparse_mod,
                                 occs = occs_lep_cal)

head(occs_sparse)
```

pam-class

Class pam Presence-Absence Matrix

Description

Class pam Presence-Absence Matrix

Value

An object of class pam

Slots

pams A list of sparse matrices representing Presence-Absence Matrix for each simulation time
 which_steps Simulation steps
 sp_names Names of species in the PAM
 grid Raster grid of the studied area
 cellIDs Cells with ids of the PAM sites

Author(s)

Luis Osorio-Olvera & Jorge Soberón

pam2bioindex

pam2bioindex: PAM to biodiversity index

Description

pam2bioindex estimates various biodiversity indices for a certain PAM.

Usage

```
pam2bioindex(pam, biodiv_index = "dispersion_field", as_sparse = FALSE)
```

Arguments

pam	A Presence-Absence-Matrix of matrix class or sparse matrix.
biodiv_index	Possible values are alpha, omega, wbeta (Whittaker's multiplicative beta index), laBeta (Lande's additive beta index) dispersion_field, all.
as_sparse	Return indices as sparse objects

Details

The biodiversity indices can be found in Soberón and Cavner (2015).

Value

An object of class `bioindex` with three slots each represents a matrix of diversity indices: alpha, omega, and dispersion field, richness_field.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberon J, Cavner J (2015). "Indices of Biodiversity Pattern Based on Presence-Absence Matrices: A GIS Implementation." *Biodiversity Informatics*, **10**, 22–34.

Examples

```

set.seed(111)
pam <- matrix(rbinom(100,1,0.3),nrow = 10,ncol = 10)
bioindices <- bamm::pam2bioindex(pam=pam,biodiv_index="all")
# Return results as sparse models
bioindices <- bamm::pam2bioindex(pam=pam,biodiv_index="all",as_sparse=TRUE)
bioindices@alpha
bioindices@omega
bioindices@dispersion_field

```

pam2richness	<i>pam2richness: Converts Presence Absence Matrix (pam object) to richness raster</i>
--------------	---

Description

Converts Presence Absence Matrix (pam object) to richness raster

Usage

```
pam2richness(pamobj, which_steps)
```

Arguments

pamobj	An object of class pam see csim2pam
which_steps	Time steps in the pam to convert

Value

A RasterStack richness for each simulation step

Author(s)

Luis Osorio-Olvera & Jorge Soberón.

Examples

```

lagos_path <- system.file("extdata/conejos",
                          package = "bamm")
enm_path <- list.files(lagos_path,
                      pattern = ".tif",
                      full.names = TRUE)[seq(1,10)]
en_models <- raster::stack(enm_path)
ngbs_vect <- sample(2,replace = TRUE,
                  size = raster::nlayers(en_models))
init_coords <- read.csv(file.path(lagos_path,
                                "lagos_initit.csv"))[seq(1,10),]
nsteps <- 10
sdm_comm <- bamm::community_sim(en_models = en_models,

```

```

ngbs_vect = ngbs_vect,
init_coords = init_coords,
nsteps = nsteps,
threshold = 0.1)

pams <- bamm::csim2pam(community_sim = sdm_comm ,
                      which_steps = seq_len(nsteps))
richness_stack <- bamm::pam2richness(pamobj = pams,
                                   which_steps = pams@which_steps)
raster::plot(richness_stack)

```

permute_pam

*permute_pam: Function to permute a Presence-Absence-Matrix.***Description**

permute_pam: Function to permute a Presence-Absence-Matrix.

Usage

```
permute_pam(m, niter = NULL, as_sparse = FALSE, randal = "fastball")
```

Arguments

m	Presence-Absence-Matrix (PAM) or a binary matrix with columns representing species and rows sites.
niter	Number of iterations to permute the PAM.
as_sparse	If TRUE the PAM will be returned as a sparse matrix
randal	Randomization algorithm applied to the PAM. Possible choices "curveball", "fastball", and "indep_swap".

Details

This function can use the "curveball" (Strona et al., 2014), the fastball (Godard and Neal, 2022), and the independent swap algorithms. The implementation of the "fastball" in C++ is provided in <https://github.com/zpneal/fastball/blob/main/fastball.cpp>. Please when using the "fastball" algorithm for publications cite Godard and Neal (2022). When using the "curveball" cite Strona et al. (2014). When using independent swap ("indep_swap") cite Kembel et al. (2010)

Value

Returns a permuted matrix of the same dimensions of m (same number of rows and columns). Note that the sum of each row and column of this permuted matrix is equal to that of m. species.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

- Strona G, Nappo D, Boccacci F, Fattorini S, San-Miguel-Ayanz J (2014). “A fast and unbiased procedure to randomize ecological binary matrices with fixed row and column totals.” *Nature Communications*, **5**(1), 1–9. ISSN 20411723, doi:10.1038/ncomms5114, <https://www.r-project.org>.
- Godard K, Neal ZP (2022). “fastball: a fast algorithm to randomly sample bipartite graphs with fixed degree sequences.” *Journal of Complex Networks*, **10**(6), cnac049. ISSN 2051-1329, doi:10.1093/comnet/cnac049, <https://academic.oup.com/comnet/article-pdf/10/6/cnac049/47758701/cnac049.pdf>.
- Kembel SW, Cowan PD, Helmus MR, Cornwell WK, Morlon H, Ackerly DD, Blomberg SP, Webb CO (2010). “Picante: R tools for integrating phylogenies and ecology.” *Bioinformatics*, **26**, 1463–1464.

Examples

```
set.seed(111)
pam <- matrix(rbinom(100,1,0.3),nrow = 10,ncol = 10)
ppam <- bamm::permute_pam(m = pam,niter = NULL,as_sparse = FALSE)
# Check if matrices are different
all(pam == ppam)
# Check if row totals are the same
all(Matrix::rowSums(pam) == Matrix::rowSums(ppam))
# Check if column total are the same
all(Matrix::colSums(pam) == Matrix::colSums(ppam))
```

```
plot,diversity_range,ANY-method
```

Plot method for objects of class diversity_range bamm.

Description

Plot method for objects of class diversity_range **bamm**.

Usage

```
## S4 method for signature 'diversity_range,ANY'
plot(
  x,
  xlab = NULL,
  plot_type = "diversity_range",
  legend = TRUE,
  legend_position = "bottomright",
  ylab = NULL,
  col = NULL,
  pch = NULL,
  pch_legend = 19,
  radius = 0.5,
  ...
)
```

Arguments

x	An object of class <code>diversity_range</code>
xlab	x label
plot_type	Plot type: possible options: "diversity_range" (range-diversity plot), "diversity_range_map" (a raster map with <code>diversity_range</code> categories), "alpha" (a raster map with alpha diversity values), "dispersion_field" (a raster with dispersion field)
legend	Logical. If TRUE the legend of the categorical diversity range values will appear.
legend_position	Legend position.
ylab	y label
col	Plot colors.
pch	Patch type.
pch_legend	Patch type for legends.
radius	Size of the patch for the interactive map.
...	Graphical parameters. Any argument that can be passed to 1) <code>base::plot</code> , such as <code>axes=FALSE</code> , <code>main='title'</code> , <code>ylab='latitude'</code> 2) <code>leaflet::leaflet</code> or 3) <code>leaflet::addCircleMarkers</code> .

Details

To show interactive `diversity_range` plots install the 'plotly' R package.

Value

Plot of the results of the `diversity_range` analysis

Author(s)

Luis Osorio-Olvera & Jorge Soberón

pol2pam

Convert distribution polygons to a presence-absence matrix (PAM)

Description

This function takes spatial polygon objects (typically species distribution polygons) and converts them into a presence-absence matrix (PAM) using a rasterization approach at a specified resolution. The function is particularly useful for biodiversity and biogeography analyses.

Usage

```
pol2pam(poly, taxon_attribute, resolution, polymask = NULL)
```

Arguments

poly	Spatial polygon object (SpatialPolygonsDataFrame, sf, etc.) containing species or taxon distribution data.
taxon_attribute	Character. The name of the column in 'poly' that contains taxon identifiers (species, genera, etc.).
resolution	Numeric. The resolution for the output raster in coordinate system units (cell size).
polymask	Optional. A spatial polygon object used to mask and crop the resulting raster. If NULL, no masking is applied.

Details

The function works by:

1. Creating a base raster with the specified resolution and extent
2. Splitting polygons by taxon attribute
3. Rasterizing each taxon's distribution using exact extraction
4. Stacking individual rasters into a multi-layer raster
5. Applying optional masking with polymask
6. Converting the raster stack to a PAM using `bamm::models2pam`

Value

A PAM (Presence-Absence Matrix) object of class 'pam' from the 'bamm' package containing:

- `matrix`: Presence-absence matrix (1/0) where rows represent grid cells and columns represent taxa
- `richness`: Richness pattern across grid cells
- `sparse`: Logical indicating if the matrix is stored in sparse format
- `cell_coordinates`: Coordinates of each grid cell

Note

This function requires the following packages: `raster`, `exactextractr`, `purrr`, and `bamm`. The input polygons are converted to `SpatialPolygonsDataFrame` if they aren't already.

See Also

[models2pam](#), [raster](#), [exact_extract](#)

Examples

```
## Not run:
# Load required libraries
library(raster)

# Example with sample data
uicn <- readRDS(system.file("extdata/uicn.rds",package = "bamm"))
sudam <- readRDS(system.file("extdata/suam.rds",package = "bamm"))
# Convert to PAM with 0.5 degree resolution
pam_result <- bamm::pol2pam(poly = uicn,
                           taxon_attribute = "binomial",
                           resolution = 0.5,
                           polymask = NULL)

# With masking polygon
pam_masked <- pol2pam(poly = uicn,
                     taxon_attribute = "binomial",
                     resolution = 0.5,
                     polymask = sudam)

## End(Not run)
```

predict,bam-method	<i>Predict method of the package bamm.</i>
--------------------	---

Description

predicts species' distribution under suitability changes

Usage

```
## S4 method for signature 'bam'
predict(
  object,
  niche_layers,
  nbgs_vec = NULL,
  nsteps_vec,
  stochastic_dispersal = FALSE,
  disp_prop2_suitability = TRUE,
  disper_prop = 0.5,
  animate = FALSE,
  period_names = NULL,
  fmt = "GIF",
  filename,
  bg_color = "#F6F2E5",
  suit_color = "#0076BE",
  occupied_color = "#03C33F",
```

```

    png_keyword = "sdm_sim",
    ani.width = 1200,
    ani.height = 1200,
    ani.res = 300
  )

```

Arguments

<code>object</code>	a of class bam.
<code>niche_layers</code>	A raster or RasterStack with the niche models for each time period
<code>nbgs_vec</code>	A vector with the number of neighbors for the adjacency matrices
<code>nsteps_vec</code>	Number of simulation steps for each time period.
<code>stochastic_dispersal</code>	Logical. If dispersal depends on a probability of visiting neighbor cells (Moore neighborhood).
<code>disp_prop2_suitability</code>	Logical. If probability of dispersal is proportional to the suitability of reachable cells. The proportional value must be declared in the parameter ‘ <code>disper_prop</code> ’.
<code>disper_prop</code>	Probability of dispersal to reachable cells.
<code>animate</code>	Logical. If TRUE a dispersal animation on climate change scenarios will be created
<code>period_names</code>	Character vector with the names of periods that will be animated. Default NULL.
<code>fmt</code>	Animation format. Possible values are GIF and HTML
<code>filename</code>	File name.
<code>bg_color</code>	Color for unsuitable pixels. Default "#F6F2E5".
<code>suit_color</code>	Color for suitable pixels. Default "#0076BE".
<code>occupied_color</code>	Color for occupied pixels. Default "#03C33F".
<code>png_keyword</code>	A keyword name for the png images generated by the function
<code>ani.width</code>	Animation width unit in px
<code>ani.height</code>	Animation height unit in px
<code>ani.res</code>	Animation resolution unit in px

Value

A RasterStack of predictions of dispersal dynamics as a function of environmental change scenarios.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

Examples

```
# rm(list = ls())
# Read raster model for Lepus californicus
model_path <- system.file("extdata/Lepus_californicus_cont.tif",
                           package = "bamm")
model <- raster::raster(model_path)
# Convert model to sparse
sparse_mod <- bamm::model2sparse(model = model, threshold=0.1)
# Compute adjacency matrix
adj_mod <- bamm::adj_mat(sparse_mod, ngbs=1)

# Initial points to start dispersal process

occs_lep_cal <- data.frame(longitude = c(-115.10417,
                                         -104.90417),
                           latitude = c(29.61846,
                                         29.81846))

# Convert to sparse the initial points
occs_sparse <- bamm::occs2sparse(modelsparse = sparse_mod,
                                 occs = occs_lep_cal)

# Run the bam (sdm) simulation for 100 time steps
smd_lep_cal <- bamm::sdm_sim(set_A = sparse_mod,
                             set_M = adj_mod,
                             initial_points = occs_sparse,
                             nsteps = 10)

#-----
# Predict species' distribution under suitability change
# scenarios (could be climate change scenarios).
#-----

# Read suitability layers (two suitability change scenarios)
layers_path <- system.file("extdata/suit_change",
                           package = "bamm")
niche_mods_stack <- raster::stack(list.files(layers_path,
                                             pattern = ".tif$",
                                             full.names = TRUE))

raster::plot(niche_mods_stack)
# Predict
new_preds <- predict(object = smd_lep_cal,
                     niche_layers = niche_mods_stack,
                     nsteps_vec = c(50,100))

# Generate the dispersal animation for time period 1 and 2

if(requireNamespace("animation")){
  ani_prd <- tempfile(pattern = "prediction_", fileext = ".gif")
  #new_preds <- predict(object = smd_lep_cal,
  #                    niche_layers = niche_mods_stack,
  #                    nsteps_vec = c(10,10),
  #                    animate=TRUE,
  #                    filename=ani_prd,
```

```
#           fmt="GIF")

}
```

sdm_sim	<i>sdm_sim: Simulate single species dispersal dynamics using the BAM framework.</i>
---------	---

Description

sdm_sim: Simulate single species dispersal dynamics using the BAM framework.

Usage

```
sdm_sim(
  set_A,
  set_M,
  sp_interaction_model = NULL,
  initial_points,
  nsteps,
  stochastic_dispersal = TRUE,
  disp_prop2_suitability = TRUE,
  disper_prop = 0.5,
  progress_bar = TRUE,
  rcpp = TRUE
)
```

Arguments

set_A	A setA object returned by the function model2sparse
set_M	A setM object containing the adjacency matrix of the study area. See adj_mat
sp_interaction_model	A RasterLayer representing a suitability model of a species positive interaction. See details
initial_points	A sparse vector returned by the function occs2sparse
nsteps	Number of steps to run the simulation
stochastic_dispersal	Logical. If dispersal depends on a probability of visiting neighbor cells (Moore neighborhood).
disp_prop2_suitability	Logical. If probability of dispersal is proportional to the suitability of reachable cells. The proportional value must be declared in the parameter ‘disper_prop’.
disper_prop	Probability of dispersal to reachable cells.
progress_bar	Show progress bar
rcpp	Logical. Use native C++ code to run the model.

Details

The model is cellular automata where the occupied area of a species at time $t + 1$ is estimated by the multiplication of two binary matrices: one matrix represents movements (M), another abiotic -niche- tolerances (A) (Soberon and Osorio-Olvera, 2022).

$$\mathbf{G}_j(t + 1) = \mathbf{A}_j(t)\mathbf{M}_j\mathbf{G}_j(t)$$

The equation describes a very simple process: To find the occupied patches in $t + 1$ start with those occupied at time t denoted by $\mathbf{G}_j(t)$, allow the individuals to disperse among adjacent patches, as defined by $\mathbf{M}_j$, then remove individuals from patches that are unsuitable, as defined by $\mathbf{A}_j(t)$.

The stochastic model uses a suitability values to model dispersal probabilities. These suitability values can be either obtained from the continuous model stored in the `set_A` object or from the `sp_interaction_model` (RasterLayer). If the parameter `rcpp` is set to `TRUE` the model will be run using native C++ code through `Rcpp` and `RcppArmadillo` packages.

Value

An object of class `bam` with simulation results. The simulation are stored in the `sdm_sim` slot (a list of sparse matrices).

Author(s)

Luis Osorio-Olvera & Jorge Soberón

References

Soberón J, Osorio-Olvera L (2023). "A dynamic theory of the area of distribution." *Journal of Biogeography* 6, 50, 1037-1048. doi:10.1111/jbi.14587, <https://onlinelibrary.wiley.com/doi/abs/10.1111/jbi.14587..>

Examples

```
model_path <- system.file("extdata/Lepus_californicus_cont.tif",
  package = "bamm")
model <- raster::raster(model_path)

sparse_mod <- bamm::model2sparse(model, threshold=0.05)
adj_mod <- bamm::adj_mat(sparse_mod, nbs=1)
occs_lep_cal <- data.frame(longitude = c(-110.08880,
  -98.89638),
  latitude = c(30.43455,
  25.19919))

occs_sparse <- bamm::occs2sparse(model_sparse = sparse_mod,
  occs = occs_lep_cal)
sdm_lep_cal <- bamm::sdm_sim(set_A = sparse_mod,
  set_M = adj_mod,
  initial_points = occs_sparse,
  nsteps = 100,
  stochastic_dispersal = TRUE,
  disp_prop2_suitability=FALSE,
```

```

                                disper_prop=0.5,
                                progress_bar=TRUE)

sim_res <- bamm::sim2Raster(sdm_lep_cal)
raster::plot(sim_res)

```

setA-class

Class for the A (Abiotic) Set of BAM Diagram

Description

Represents the abiotic component (environmental suitability) in the BAM framework. Contains raster-based niche models and their sparse matrix representations.

Value

An object of class setA `showClass("setA")`

Slots

`niche_model` A `RasterLayer` or `RasterStack` representing the environmental suitability model (binary or continuous)

`suit_threshold` Numeric value used to binarize continuous models

`cellIDs` Numeric vector of raster cell IDs with non-NA values

`suit_values` Numeric vector of suitability values for continuous models

`sparse_model` A sparse matrix (`dgCMatrix`) representation of the niche model

Validity

The `niche_model` slot must be either a `RasterLayer` or `RasterStack`.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

See Also

[model2sparse](#), [setM-class](#)

setM-class	<i>Class for the M set of the bamm diagram</i>
------------	--

Description

Class for the M set of the bamm diagram

Value

An object of class setM

Slots

adj_matix An adjacency matrix
 adj_list An adjacency list
 initial_points A presence-absence vector with species' occurrences
 n_initial_points Number of initial points used to start the dispersal process
 ngbs Number of neighbors

Author(s)

Luis Osorio-Olvera & Jorge Soberón

Examples

```
showClass("setM")
```

shape2Grid	<i>shape2Grid: Function to create a grid given a spatial polygon</i>
------------	--

Description

shape2Grid creates a raster grid given a spatial polygon and a grid resolution.

Usage

```
shape2Grid(shpolygon, resolution, ones = TRUE)
```

Arguments

shpolygon	A SpatialPolygon, SpatialPolygonDataFrame representing the desired shape of the grid.
resolution	Numeric. Spatial resolution of the grid.
ones	Logical. Fill with ones the values of the raster. If not the values will be written as cellID values.

Value

Returns a raster object with the shape of 'shpolygon' of a given resolution.

Author(s)

Luis Osorio-Olvera & Jorge Soberón

Examples

```
x_coord <- c(-106.5699, -111.3737, -113.9332, -110.8913, -106.4262, -106.5699)
y_coord <- c(16.62661, 17.72373, 19.87618, 22.50763, 21.37728, 16.62661)
xy <- cbind(x_coord, y_coord)
p <- sp::Polygon(xy)
ps <- sp::Polygons(list(p),1)
sps <- sp::SpatialPolygons(list(ps))
r1 <- bamm::shape2Grid(sps,resolution = 0.1,ones = FALSE)
plot(r1)
sp::plot(sps,add=TRUE)
```

show,setA-method

*Show information in setA class **bamm**.*

Description

Show information in setA class **bamm**.

Show information in csd class **bamm**.

Show information in pam class **bamm**.

Show information in pam class **bamm**.

Show information in setA class **bamm**.

Show information in diversity_range class **bamm**.

Usage

```
## S4 method for signature 'setA'
show(object)
```

```
## S4 method for signature 'csd'
show(object)
```

```
## S4 method for signature 'pam'
show(object)
```

```
## S4 method for signature 'bioindex_sparse'
show(object)
```

```
## S4 method for signature 'setM'
show(object)

## S4 method for signature 'diversity_range'
show(object)
```

Arguments

object An object of class diversity_range

Value

Display information about the setA object
 Display information about the csd object
 Display information about the pam object
 Display information about the bioindex_spars object
 Display information about the setM object
 Display information about the diversity_range object

Author(s)

Luis Osorio-Olvera & Jorge Soberón

sim2Animation	<i>sim2Animation: Animate BAM simulation object.</i>
---------------	--

Description

Animates BAM simulation object.

Usage

```
sim2Animation(
  sdm_simul,
  which_steps,
  fmt = "GIF",
  filename,
  png_keyword = NULL,
  extra_legend = NULL,
  bg_color = "#F6F2E5",
  suit_color = "#0076BE",
  occupied_color = "#03C33F",
  gif_vel = 0.8,
  ani.width = 1200,
  ani.height = 1200,
  ani.res = 300
)
```



```

nsteps = 50)

if(requireNamespace("animation")){
  ani_name <- tempfile(pattern = "simulation_",fileext = ".html")
  #sdm_lep_cal_st <- bamm::sim2Animation(sdm_simul = sdm_lep_cal,
  #                                     which_steps = seq(1,50,by=1),
  #                                     fmt = "HTML",ani.width = 1200,
  #                                     ani.height = 1200,
  #                                     filename = ani_name)
}

```

sim2Raster

sim2Raster: Convert a BAM simulation object to RasterStack

Description

Convert a BAM simulation object to RasterStack.

Usage

```
sim2Raster(sdm_simul, which_steps = NULL, progress_bar = TRUE)
```

Arguments

sdm_simul	A bam object. See sdm_sim
which_steps	A numeric vector indicating the simulation steps that are going to be converted into raster layers.
progress_bar	Show progress bar

Value

A RasterStack of species' distribution at each simulation step

Author(s)

Luis Osorio-Olvera & Jorge Soberón

Examples

```

model_path <- system.file("extdata/Lepus_californicus_cont.tif",
                           package = "bamm")
model <- raster::raster(model_path)
sparse_mod <- bamm::model2sparse(model, threshold=0.1)
adj_mod <- bamm::adj_mat(sparse_mod,ngbs = 1)
occs_lep_cal <- data.frame(longitude = c(-115.10417,
                                         -104.90417),
                           latitude = c(29.61846,
                                         29.81846))

```

```
occs_sparse <- bamm::occs2sparse(modelsparse = sparse_mod,  
                                occs = occs_lep_cal)  
sdm_lep_cal <- bamm::sdm_sim(set_A = sparse_mod,  
                             set_M = adj_mod,  
                             initial_points = occs_sparse,  
                             nsteps = 10)  
sdm_lep_cal_st <- bamm::sim2Raster(sdm_simul = sdm_lep_cal,  
                                  which_steps = seq(1,10,by=1))  
  
raster::plot(sdm_lep_cal_st)
```

Index

A-class (setA-class), 39
adj_mat, 3, 7, 9, 12, 37

bam, 13, 38
bam (bam-class), 5
bam-class, 5
bam-method (predict, bam-method), 34
bam_clusters, 6, 15
bam_sim, 7
bam_ssim, 9
biodiversity_index (bioindex-class), 11
biodiversity_index_sparse
 (bioindex_sparse-class), 11
bioindex, 28
bioindex (bioindex-class), 11
bioindex-class, 11
bioindex_sparse
 (bioindex_sparse-class), 11
bioindex_sparse-class, 11

community-class (community_sim-class),
 14
community_bam, 16
community_bam (community_sim-class), 14
community_sim, 12, 16
community_sim-class, 14
csd, 6
csd (csd-class), 14
csd-class, 14
csd_estimate, 15
csim2pam, 16, 29

diversity_range, 18, 19
diversity_range
 (diversity_range-class), 17
diversity_range-class, 17
diversity_range_analysis, 18
diversityrange (diversity_range-class),
 17

eigen_bam, 20

eigs, 4
exact_extract, 33

g_area (g_area-class), 21
g_area-class, 21

jaccard, 22

leaflet (leaflet-class), 23
leaflet-class, 23

M-class (setM-class), 40
model2sparse, 3, 4, 6, 22, 23, 27, 37, 39
models2pam, 24, 33

null_dispersion_field_distribution, 18,
 25

occs2sparse, 7, 9, 26, 37

PAM (pam-class), 27
pam, 16
pam (pam-class), 27
pam-class, 27
pam2bioindex, 28
pam2richness, 29
permute_pam, 26, 30
plot, 18, 19
plot, diversity_range, ANY-method, 31
pol2pam, 32
predict (predict, bam-method), 34
predict, bam-method, 34

raster, 33

sdm_sim, 13, 37, 43, 44
setA, 6, 8, 10, 23
setA (setA-class), 39
setA-class, 39
setM, 4, 8, 10
setM (setM-class), 40

setM-class, [40](#)
shape2Grid, [40](#)
show, bioindex_sparse-method
 (show, setA-method), [41](#)
show, csd-method (show, setA-method), [41](#)
show, diversity_range-method
 (show, setA-method), [41](#)
show, pam-method (show, setA-method), [41](#)
show, setA-method, [41](#)
show, setM-method (show, setA-method), [41](#)
sim2Animation, [42](#)
sim2Raster, [44](#)