

# The flexisym package

Authors: Michael J. Downes, Morten Høgholm  
Maintained by Morten Høgholm, Will Robertson  
Feedback: <https://github.com/wspr/breqn/issues>

2020/02/16 0.98h

## User's guide

For now, the user's guide is in breqn.

## Implementation

### 1 flexisym

```
1 <*package>
2 \RequirePackage{expl3}[2009/08/05]
3 \ProvidesExplPackage{flexisym}{2020/02/16}{0.98h}{Make math characters macros}
4
5 \edef\do{%
6   \noexpand\AtEndOfPackage{%
7     \catcode\number'\="\number\catcode'\"
8     \relax
9   }%
10 }
11 \do \let\do\relax
12 \catcode'\="=12
13 \let\@sym\@gobble
14 \DeclareOption{robust}{%
15   \def\@sym#1{%
16     \ifx\protect\@typeset@protect \else\protect#1\exp_after:wN\use_none:nnnn\fi
17   }%
18 }
```

The math groups (mg) here relate to `\textfontn`.

```
19 \def\mg@bin{2}% binary operators
20 \def\mg@rel{2}% relations
21 %%\def\mg@nre{B}% negated relations
22 \def\mg@del{3}% delimiters
```

```

23 %%\def\mg@arr{B}% arrows
24 \def\mg@acc{0}% accents
25 \def\mg@cop{3}% cumulative operators (sum, int)
26 \def\mg@latin{1}% (Latin) letters
27 \def\mg@greek{1}% (lowercase) Greek
28 \def\mg@Greek{0}% (capital) Greek
29 %%\def\mg@bflatin{4}% bold upright Latin letters ?
30 %%\def\mg@Bbb{B}% blackboard bold
31 \def\mg@cal{2}% script/calligraphic
32 %%\def\mg@frak{5}% Fraktur letters
33 \def\mg@digit{0}% decimal digits % 1 = oldstyle, 0 = capital

```

This is how we insert mathchars. The command has three arguments: class, fam and slot position and so it is always given as hexadecimal. This way of separating things should make it easier to get this to work with XeTeX et al. which have many more slot positions

```

34 \cs_set_protected:Nn \math_char:Nnn {
35   \tex_mathchar:D \__int_eval:w " #1#2#3 \__int_eval_end:
36 }

```

Delimiters and radicals are similar except here we have both small and large variant. Radicals have no class.

```

37 \cs_set_protected:Nn \math_delimiter:NnnNn {
38   \tex_delimiter:D \__int_eval:w " #1#2#3#4#5 \__int_eval_end:
39 }
40 \cs_set_protected:Nn \math_radical:NnnNn {
41   \tex_radical:D \__int_eval:w " #1#2#3#4 \__int_eval_end:
42 }
43 \cs_set_protected:Nn \math_accent:Nnnnn {
44   \tex_mathaccent:D \__int_eval:w " #1 #2 #3 \__int_eval_end: {#4}
45 }
46
47 \let\sumlimits\displaylimits
48 \let\intlimits\nolimits
49 \let\name\limits\displaylimits

```

TeX defines eight types of atoms.

0. Ordinary
1. Operators
2. Binary
3. Relation
4. Open
5. Close
6. Punctuation
7. Inner

TeX defines eight math classes.

0. Ordinary
1. Operators
2. Binary
3. Relation
4. Open
5. Close
6. Punctuation
7. Variable family

flexisym/breqn extends this to types of classes.

0. Ordinary: (Ord), Bidirectional delimiters (DeB), Radicals (Rad), Accented items (Acc)
1. Operators: Cumulative Operators sum-like (COs), Cumulative Operators integral-like (COi)
2. Binary: (Bin)
3. Relation: (Rel), Arrow delimiters (DeA)
4. Open: (DeL)
5. Close (DeR)
6. Punctuation: (Pun)
7. Variable family: (Var)

Here's an overview of what we are about to do. Math chars of each type as defined by us need a basic operation for inserting it. We will call that function `\math_bsym_⟨type⟩:Nn`. Next there are compund symbols for each type which we name `\math_bcsym_⟨type⟩:Nn`. Also, there is inline mode and display mode which are different. We will call them for `\math_ism_⟨type⟩:Nn` and `\math_icsym_⟨type⟩:Nn` for inline mode and `\math_dsym_⟨type⟩:Nn` and `\math_dcsym_⟨type⟩:Nn`. The code uses the terms `\math_sym_⟨type⟩:Nn` and `\math_csym_⟨type⟩:Nn` for the current meaning of things. First up the basic definitions. #1 is the math group it is from and #2 is the slot position.

```

50 \cs_new:Npn \math_bsym_Ord:Nn {\math_char:NNn 0 }% \m@Ord
51 \cs_new:Npn \math_bsym_Var:Nn {\math_char:NNn 7 }% \m@Var
52 \cs_new:Npn \math_bsym_Bin:Nn {\math_char:NNn 2 }% \m@Bin
53 \cs_new:Npn \math_bsym_Rel:Nn {\math_char:NNn 3 }% \m@Bin
54 \cs_new:Npn \math_bsym_Pun:Nn {\math_char:NNn 6 }% \m@Pun

```

```

55 \cs_new:Nn \math_bsym_COs:Nn { \math_char:NNn 1 #1 {#2} \sumlimits }% \m@COs
56 \cs_new:Nn \math_bsym_COi:Nn { \math_char:NNn 1 #1 {#2} \intlimits }% \m@COi
57 \cs_new:Nn \math_bsym_DeL:Nn { \math_sd_del_aux:Nnn 4 #1{#2} }% \m@DeL
58 \cs_new:Nn \math_bsym_DeR:Nn { \math_sd_del_aux:Nnn 5 #1{#2} }% \m@DeR
59 \cs_new:Nn \math_bsym_DeB:Nn { \math_sd_del_aux:Nnn 0 #1{#2} }% \m@DeB
60 \cs_new:Nn \math_bsym_DeA:Nn { \math_sd_del_aux:Nnn 3 #1{#2} }% \m@DeA
61 \cs_new:Nn \math_bsym_Rad:Nn { \math_sd_rad_aux:Nn #1{#2} }% \m@Rad
62 \cs_new:Npn \math_bsym_Acc:Nn #1#2#3#4 { \math_accent:NNnn #1#2{#3}{#4}}% name is wrong
63

```

Next is somewhat complicated internally. The way it is done is that delimiters and radicals need information about the smallest version of the symbol. If this smallest delimiter (SD) is defined, then use it. We have these functions to help us return the number. Extract the numbers to use and stick a function in front of it.

Code changed because now we require the smallest delimiter to be defined (it may be the same, no problem in that). So the two arguments present in `\math_bsym_DeL:Nn` are the location of extensible version (where the font will do the rest for us automatically). For each delimiter, a pointer is defined using the extensible characters family and slot as name and value equal to family and position of the smallest version. For  $\langle$  in standard L<sup>A</sup>T<sub>E</sub>X this is `{del}{00}` and `{OT1}{28}` respectively. Hence, `\math_bsym_DeL:Nn \mg@del {00}` must expand to `\math_delimiter:NNnNn 4 \mg@OT1 {28}\mg@del{00}`. So first expand away to get to the smallest version. Then call next function which shuffles the arguments around.

```

64 \cs_set:Npn \math_sd_del_aux:Nnn #1#2#3{
65   \exp_args:Nf \math_sd_del_auxi:nN {\use:c{sd@#2#3}} #1 #2{#3}
66 }
67 \cs_set:Npn \math_sd_del_auxi:nN #1#2{ \math_delimiter:NNnNn #2 #1 }

```

Same for radicals.

```

68 \cs_set:Npn \math_sd_rad_aux:Nn #1#2{
69   \exp_args:Nf \math_sd_rad_auxi:n {\use:c{sd@#1#2}} #1 {#2}
70 }
71 \cs_set:Npn \math_sd_rad_auxi:n #1{ \math_radical:NnNn #1 }
72
73
74 % \cs_set:Npn \math_sd_aux:nn #1#2 {
75 %   %\exp_args:Nnf \use:nn { #1} { \math_sd_auxi:Nn #2 }
76 %   \exp_args:Nnf \use:nn { #1} { \use:c{sd@\use:nn#2} }
77 % }
78 % \cs_set:Npn \math_sd_auxi:Nn #1#2 {
79 %   \cs_if_free:cTF {sd@#1#2}
80 %   { #1{#2} }
81 %   { \use:c{sd@#1#2} }
82 % }

```

compound symbols here

```

83 \cs_set_protected:Npn \math_bcsym_Ord:Nn #1#2 { \@syntype \mathord { \OrdSymbol {#2} } }%
84 \cs_set_protected:Npn \math_bcsym_Var:Nn #1#2 { \@syntype \mathord { \OrdSymbol {#2} } }%
85 \cs_set_protected:Npn \math_bcsym_Bin:Nn #1#2 { \@syntype \mathbin { \OrdSymbol {#2} } }%

```

```

86 \cs_set_protected:Npn \math_bcsym_Rel:Nn #1#2 { \@syntype \mathrel { \OrdSymbol {#2} } }%
87 \cs_set_protected:Npn \math_bcsym_Pun:Nn #1#2 { \@syntype \mathpunct { \OrdSymbol {#2} } }%
88 \cs_set_protected:Npn \math_bcsym_COi:Nn #1#2 { \@syntype \mathop { \OrdSymbol {#2} \intl
89 \cs_set_protected:Npn \math_bcsym_COs:Nn #1#2 { \@syntype \mathop { \OrdSymbol {#2} \suml
90 \cs_set_protected:Npn \math_bcsym_DeL:Nn #1#2 { \@syntype \mathopen { \OrdSymbol {#2} } }%
91 \cs_set_protected:Npn \math_bcsym_DeR:Nn #1#2 { \@syntype \mathclose { \OrdSymbol {#2} } }%
92 \cs_set_protected:Npn \math_bcsym_DeB:Nn #1#2 { \@syntype \mathord { \OrdSymbol {#2} } }%
93 \cs_set_protected:Npn \math_bcsym_DeA:Nn #1#2 { \@syntype \mathrel { \OrdSymbol {#2} } }%
94 \cs_set_protected:Npn \math_bcsym_Acc:Nn { \@sym}%\@symAcc FIX!
95 % These three?
96 \cs_set_protected:Npn \math_bcsym_Ope:Nn #1#2{\@syntype\mathopen{\OrdSymbol{#2}}}%\@symVar
97 \cs_set_protected:Npn \math_bcsym_Clo:Nn #1#2{\@syntype\mathclose{\OrdSymbol{#2}}}%\@symVar
98 \cs_set_protected:Npn \math_bcsym_Inn:Nn #1#2{\@syntype\mathinner{\OrdSymbol{#2}}}%\@symVar
99
100 \let\@syntype\@firstofone
101 \let\sym@global\global

```

The inline variants, using the basic operations. Currently we do not do anything to inline math.

```

102 \cs_new:Npn \math_isym_Ord:Nn { \math_bsym_Ord:Nn }% \m@Ord
103 \cs_new:Npn \math_isym_Var:Nn { \math_bsym_Var:Nn }% \m@Var
104 \cs_new:Npn \math_isym_Bin:Nn { \math_bsym_Bin:Nn }% \m@Bin
105 \cs_new:Npn \math_isym_Rel:Nn { \math_bsym_Rel:Nn }% \m@Bin
106 \cs_new:Npn \math_isym_Pun:Nn { \math_bsym_Pun:Nn }% \m@Pun
107 \cs_new:Npn \math_isym_COs:Nn { \math_bsym_COs:Nn }% \m@COs
108 \cs_new:Npn \math_isym_COi:Nn { \math_bsym_COi:Nn }% \m@COi
109 \cs_new:Npn \math_isym_DeL:Nn { \math_bsym_DeL:Nn }% \m@DeL
110 \cs_new:Npn \math_isym_DeR:Nn { \math_bsym_DeR:Nn }% \m@DeR
111 \cs_new:Npn \math_isym_DeB:Nn { \math_bsym_DeB:Nn }% \m@DeB
112 \cs_new:Npn \math_isym_DeA:Nn { \math_bsym_DeA:Nn }% \m@DeA
113 \cs_new:Npn \math_isym_Rad:Nn { \math_bsym_Rad:Nn }% \m@Rad
114 \cs_new:Npn \math_isym_Acc:Nn { \math_bsym_DeL:Nn }% name is wrong
115 % inline compound
116 \cs_set_protected:Npn \math_icsym_Ord:Nn { \math_bcsym_Ord:Nn }
117 \cs_set_protected:Npn \math_icsym_Var:Nn { \math_bcsym_Var:Nn }
118 \cs_set_protected:Npn \math_icsym_Bin:Nn { \math_bcsym_Bin:Nn }
119 \cs_set_protected:Npn \math_icsym_Rel:Nn { \math_bcsym_Rel:Nn }
120 \cs_set_protected:Npn \math_icsym_Pun:Nn { \math_bcsym_Pun:Nn }
121 \cs_set_protected:Npn \math_icsym_COi:Nn { \math_bcsym_COi:Nn }
122 \cs_set_protected:Npn \math_icsym_COs:Nn { \math_bcsym_COs:Nn }
123 \cs_set_protected:Npn \math_icsym_DeL:Nn { \math_bcsym_DeL:Nn }
124 \cs_set_protected:Npn \math_icsym_DeR:Nn { \math_bcsym_DeR:Nn }
125 \cs_set_protected:Npn \math_icsym_DeB:Nn { \math_bcsym_DeB:Nn }
126 \cs_set_protected:Npn \math_icsym_DeA:Nn { \math_bcsym_DeA:Nn }
127 \cs_set_protected:Npn \math_icsym_Acc:Nn { \math_bcsym_Acc:Nn }
128 \cs_set_protected:Npn \math_icsym_Ope:Nn { \math_bcsym_Ope:Nn }
129 \cs_set_protected:Npn \math_icsym_Clo:Nn { \math_bcsym_Clo:Nn }
130 \cs_set_protected:Npn \math_icsym_Inn:Nn { \math_bcsym_Inn:Nn }

```

The display variants, using the basic operations. Currently we do not do

anything to inline math.

```

131 \cs_new:Npn \math_dsym_Ord:Nn { \math_bsym_Ord:Nn }
132 \cs_new:Npn \math_dsym_Var:Nn { \math_bsym_Var:Nn }
133 \cs_new:Npn \math_dsym_Bin:Nn { \math_bsym_Bin:Nn }
134 \cs_new:Npn \math_dsym_Rel:Nn { \math_bsym_Rel:Nn }
135 \cs_new:Npn \math_dsym_Pun:Nn { \math_bsym_Pun:Nn }
136 \cs_new:Npn \math_dsym_COs:Nn { \math_bsym_COs:Nn }
137 \cs_new:Npn \math_dsym_COi:Nn { \math_bsym_COi:Nn }
138 \cs_new:Npn \math_dsym_DeL:Nn { \math_bsym_DeL:Nn }
139 \cs_new:Npn \math_dsym_DeR:Nn { \math_bsym_DeR:Nn }
140 \cs_new:Npn \math_dsym_DeB:Nn { \math_bsym_DeB:Nn }
141 \cs_new:Npn \math_dsym_DeA:Nn { \math_bsym_DeA:Nn }
142 \cs_new:Npn \math_dsym_Rad:Nn { \math_bsym_Rad:Nn }
143 \cs_new:Npn \math_dsym_Acc:Nn { \math_bsym_DeL:Nn }
144 % inline compound
145 \cs_set_protected:Npn \math_dcsym_Ord:Nn { \math_bcsym_Ord:Nn }
146 \cs_set_protected:Npn \math_dcsym_Var:Nn { \math_bcsym_Var:Nn }
147 \cs_set_protected:Npn \math_dcsym_Bin:Nn { \math_bcsym_Bin:Nn }
148 \cs_set_protected:Npn \math_dcsym_Rel:Nn { \math_bcsym_Rel:Nn }
149 \cs_set_protected:Npn \math_dcsym_Pun:Nn { \math_bcsym_Pun:Nn }
150 \cs_set_protected:Npn \math_dcsym_COi:Nn { \math_bcsym_COi:Nn }
151 \cs_set_protected:Npn \math_dcsym_COs:Nn { \math_bcsym_COs:Nn }
152 \cs_set_protected:Npn \math_dcsym_DeL:Nn { \math_bcsym_DeL:Nn }
153 \cs_set_protected:Npn \math_dcsym_DeR:Nn { \math_bcsym_DeR:Nn }
154 \cs_set_protected:Npn \math_dcsym_DeB:Nn { \math_bcsym_DeB:Nn }
155 \cs_set_protected:Npn \math_dcsym_DeA:Nn { \math_bcsym_DeA:Nn }
156 \cs_set_protected:Npn \math_dcsym_Acc:Nn { \math_bcsym_Acc:Nn }
157 \cs_set_protected:Npn \math_dcsym_Ope:Nn { \math_bcsym_Ope:Nn }
158 \cs_set_protected:Npn \math_dcsym_Clo:Nn { \math_bcsym_Clo:Nn }
159 \cs_set_protected:Npn \math_dcsym_Inn:Nn { \math_bcsym_Inn:Nn }

```

Almost ready now! Now just need two commands to initialize these settings.

```

160 \cs_set:Npn \math_setup_inline_symbols:
161 {
162   \cs_set_eq:NN \math_sym_Ord:Nn \math_isym_Ord:Nn
163   \cs_set_eq:NN \math_sym_Var:Nn \math_isym_Var:Nn
164   \cs_set_eq:NN \math_sym_Bin:Nn \math_isym_Bin:Nn
165   \cs_set_eq:NN \math_sym_Rel:Nn \math_isym_Rel:Nn
166   \cs_set_eq:NN \math_sym_Pun:Nn \math_isym_Pun:Nn
167   \cs_set_eq:NN \math_sym_COs:Nn \math_isym_COs:Nn
168   \cs_set_eq:NN \math_sym_COi:Nn \math_isym_COi:Nn
169   \cs_set_eq:NN \math_sym_DeL:Nn \math_isym_DeL:Nn
170   \cs_set_eq:NN \math_sym_DeR:Nn \math_isym_DeR:Nn
171   \cs_set_eq:NN \math_sym_DeB:Nn \math_isym_DeL:Nn
172   \cs_set_eq:NN \math_sym_DeA:Nn \math_isym_DeA:Nn
173   \cs_set_eq:NN \math_sym_Rad:Nn \math_isym_Rad:Nn
174   \cs_set_eq:NN \math_sym_Acc:Nn \math_isym_DeL:Nn
175   \cs_set_eq:NN \math_csym_Ord:Nn \math_icsym_Ord:Nn
176   \cs_set_eq:NN \math_csym_Var:Nn \math_icsym_Var:Nn
177   \cs_set_eq:NN \math_csym_Bin:Nn \math_icsym_Bin:Nn

```

```

178 \cs_set_eq:NN \math_csym_Rel:Nn \math_icsym_Rel:Nn
179 \cs_set_eq:NN \math_csym_Pun:Nn \math_icsym_Pun:Nn
180 \cs_set_eq:NN \math_csym_COi:Nn \math_icsym_COi:Nn
181 \cs_set_eq:NN \math_csym_COs:Nn \math_icsym_COs:Nn
182 \cs_set_eq:NN \math_csym_DeL:Nn \math_icsym_DeL:Nn
183 \cs_set_eq:NN \math_csym_DeR:Nn \math_icsym_DeR:Nn
184 \cs_set_eq:NN \math_csym_DeB:Nn \math_icsym_DeB:Nn
185 \cs_set_eq:NN \math_csym_DeA:Nn \math_icsym_DeA:Nn
186 \cs_set_eq:NN \math_csym_Acc:Nn \math_icsym_Acc:Nn
187 \cs_set_eq:NN \math_csym_Ope:Nn \math_icsym_Ope:Nn
188 \cs_set_eq:NN \math_csym_Clo:Nn \math_icsym_Clo:Nn
189 \cs_set_eq:NN \math_csym_Inn:Nn \math_icsym_Inn:Nn
190 }
191
192 \cs_set:Npn \math_setup_display_symbols:
193 {
194 \cs_set_eq:NN \math_sym_Ord:Nn \math_dsym_Ord:Nn
195 \cs_set_eq:NN \math_sym_Var:Nn \math_dsym_Var:Nn
196 \cs_set_eq:NN \math_sym_Bin:Nn \math_dsym_Bin:Nn
197 \cs_set_eq:NN \math_sym_Rel:Nn \math_dsym_Rel:Nn
198 \cs_set_eq:NN \math_sym_Pun:Nn \math_dsym_Pun:Nn
199 \cs_set_eq:NN \math_sym_COs:Nn \math_dsym_COs:Nn
200 \cs_set_eq:NN \math_sym_COi:Nn \math_dsym_COi:Nn
201 \cs_set_eq:NN \math_sym_DeL:Nn \math_dsym_DeL:Nn
202 \cs_set_eq:NN \math_sym_DeR:Nn \math_dsym_DeR:Nn
203 \cs_set_eq:NN \math_sym_DeB:Nn \math_dsym_DeL:Nn
204 \cs_set_eq:NN \math_sym_DeA:Nn \math_dsym_DeA:Nn
205 \cs_set_eq:NN \math_sym_Rad:Nn \math_dsym_Rad:Nn
206 \cs_set_eq:NN \math_sym_Acc:Nn \math_dsym_DeL:Nn
207 \cs_set_eq:NN \math_csym_Ord:Nn \math_dcsym_Ord:Nn
208 \cs_set_eq:NN \math_csym_Var:Nn \math_dcsym_Var:Nn
209 \cs_set_eq:NN \math_csym_Bin:Nn \math_dcsym_Bin:Nn
210 \cs_set_eq:NN \math_csym_Rel:Nn \math_dcsym_Rel:Nn
211 \cs_set_eq:NN \math_csym_Pun:Nn \math_dcsym_Pun:Nn
212 \cs_set_eq:NN \math_csym_COi:Nn \math_dcsym_COi:Nn
213 \cs_set_eq:NN \math_csym_COs:Nn \math_dcsym_COs:Nn
214 \cs_set_eq:NN \math_csym_DeL:Nn \math_dcsym_DeL:Nn
215 \cs_set_eq:NN \math_csym_DeR:Nn \math_dcsym_DeR:Nn
216 \cs_set_eq:NN \math_csym_DeB:Nn \math_dcsym_DeB:Nn
217 \cs_set_eq:NN \math_csym_DeA:Nn \math_dcsym_DeA:Nn
218 \cs_set_eq:NN \math_csym_Acc:Nn \math_dcsym_Acc:Nn
219 \cs_set_eq:NN \math_csym_Ope:Nn \math_dcsym_Ope:Nn
220 \cs_set_eq:NN \math_csym_Clo:Nn \math_dcsym_Clo:Nn
221 \cs_set_eq:NN \math_csym_Inn:Nn \math_dcsym_Inn:Nn
222 }

```

Phew, that was it.

Well, almost. We need to set them up for use properly. Should they be added to `\everymath`? Probably, for math within displays. However, this is a lot of extra processing which we could tackle in the display setup.

```

223 \math_setup_inline_symbols:
    Need an active character for a second. Don't rely on ~ being active!
224 \edef\tmp{\catcode\z@=\the\catcode\z@}
225 \catcode\z@=\active
226 \def\DeclareFlexSymbol#1#2#3#4{%
227   \begingroup
228   \cs_set_protected:Npx\@tempb{
229     \exp_not:N\@sym\exp_not:N#1\exp_not:c{math_sym_#2:Nn}
230     \exp_not:c{mg@#3}{#4}
231   }
232   \ifcat\exp_not:N#1\relax
233     \sym@global\let#1\@tempb
234   \else
235     \sym@global\mathcode'#1="8000\relax
236     \lccode\z@='#1\relax
237     \lowercase{\sym@global\let~\@tempb}% zero char
238   \fi
239   \endgroup
240 }
241 \tmp % restore catcode
242 \cs_set:Npn \DeclareFlexDelimiter #1#2#3#4#5#6{
243   \DeclareFlexSymbol{#1}{#2}{#3}{#4}
244   \cs_gset:cpx{sd@use:c{mg@#3}{#4}}{\exp_not:c{mg@#5}{#6}}
245 }
246
\DeclareFlexCompoundSymbol{\cdots}{\Inn}{\cdotp\cdotp\cdotp} \def\@symInn#1#2{\@symtyp
\@syntype \mathinner{\OrdSymbol{\cdotp\cdotp\cdotp}}
247 \def\DeclareFlexCompoundSymbol#1#2#3{%
248   \exp_args:NNo \DeclareRobustCommand#1{\csname math_csym_#2:Nn\endcsname#1{#3}}%
249   \sym@global\let#1#1\relax
250 }
251 \DeclareRobustCommand\textchar{\text@char\textfont}
252 \DeclareRobustCommand\scriptchar{\text@char\scriptfont}%
    Simplified the next bit because now the slot is read as one argument so no afteras-
    signment and what have you. Just drop the char directly.
253 \def\text@char@sym#1#2#3#4{% #3=fam, #4=slot
254   \begingroup
255     \cs_set_eq:NN \@sym \prg_do_nothing: % defense against infinite loops
    the next line will result in \scriptfont<num>, where #3 provides the <num>.
256     \the\text@script@char#3%
257     \char"#4\endgroup
258 }
259 \edef\tmp{\catcode\z@=\the\catcode\z@}
260 \catcode\z@=\active
261 \def\text@char#1#2{\begingroup
262   \check@mathfonts
263   \cs_set_eq:NN \text@script@char #1

```



```

264 \cs_set_eq:NN \@sym \text@char@sym
265 \cs_set_eq:NN \@symtype \use_ii:nn
266 \cs_set_eq:NN \OrdSymbol \use:n
267 \cs_set_eq:NN \ifmode \iftrue
268 \everymath{ $\use_none:n} %$
269 \def\mkern{\mskip\z@}
270 \cs_set_eq:NN\mskip\mkern
271 \ifcat\relax\noexpand#2% true if #2 is a cs.
272   #2%
273 \else
274   \lccode\z@=\expandafter'\string#2\relax
275   \lowercase{^~@}%
276 \fi
277 \endgroup
278 }
279 \tmp % restore catcode
280 \providecommand\textprime{}
281 \DeclareRobustCommand\textprime{\leavevmode
282   \raise.8ex\hbox{\text@char\scriptfont\prime}%
283 }
284 \ifundefined{resetMathstrut@}{\{%
285   \def\resetMathstrut@{%
286     \setbox\z@\hbox{\textchar\vert}%
287     \ht\Mathstrutbox@ \ht\z@ \dp\Mathstrutbox@ \dp\z@
288   }%
289 }

```

Arrow fills. changed to 7mu as in amsmath

```

290 \ifundefined{rightarrowfill@}{\{%
291   \def\rightarrowfill@#1{\m@th\setboxz@h{ $ #1 \relbar$ } \ht\z@ \z@
292     $ #1 \copy\z@ \mkern-7mu \cleaders
293       \hbox{ $ #1 \mkern-2mu \box\z@ \mkern-2mu$ } \hfill
294       \mkern-6mu \OrdSymbol{\rightarrow} $ }
295   \def\leftarrowfill@#1{\m@th\setboxz@h{ $ #1 \relbar$ } \ht\z@ \z@
296     $ #1 \OrdSymbol{\leftarrow} \mkern-6mu \cleaders
297       \hbox{ $ #1 \mkern-2mu \copy\z@ \mkern-2mu$ } \hfill
298       \mkern-7mu \box\z@ $ }
299   \def\leftrightarrowfill@#1{\m@th\setboxz@h{ $ #1 \relbar$ } \ht\z@ \z@
300     $ #1 \OrdSymbol{\leftarrow} \mkern-6mu \cleaders
301       \hbox{ $ #1 \mkern-2mu \box\z@ \mkern-2mu$ } \hfill
302       \mkern-6mu \OrdSymbol{\rightarrow} $ }
303 }

```

hey, this looks like a simple case switch...

```

304 \def\binrel@sym#1#2#3#4{%
305   \xdef\binrel@@#1{%
306     \ifx\math_sym_Ord:Nn #2 \math_csym_Ord:Nn
307     \else\ifx\math_sym_Var:Nn#2 \math_csym_Var:Nn
308     \else\ifx\math_sym_COs:Nn#2 \math_csym_COs:Nn
309     \else\ifx\math_sym_COi:Nn#2 \math_csym_COi:Nn
310     \else\ifx\math_sym_Bin:Nn#2 \math_csym_Bin:Nn

```

```

311 \else\ifx\math_sym_Rel:Nn#2 \math_csym_Rel:Nn
312 \else\ifx\math_sym_Pun:Nn#2 \math_csym_Pun:Nn
313 \else\exp_not:N\@symErr \fi\fi\fi\fi\fi\fi
314 ?{\exp_not:N\OrdSymbol{##1}}}%
315 }
316
317 \def\binrel@a{%
318 \def\math_sym_Ord:Nn#1##2{\gdef\binrel@@###1{\math_sym_Ord:Nn#1{\OrdSymbol{####1}}}}%
319 \def\math_sym_Var:Nn#1##2{\gdef\binrel@@###1{\math_sym_Var:Nn#1{\OrdSymbol{####1}}}}%
320 \def\math_sym_COs:Nn#1##2{\gdef\binrel@@###1{\math_sym_COs:Nn#1{\OrdSymbol{####1}}}}%
321 \def\math_sym_COi:Nn#1##2{\gdef\binrel@@###1{\math_sym_COi:Nn#1{\OrdSymbol{####1}}}}%
322 \def\math_sym_Bin:Nn#1##2{\gdef\binrel@@###1{\math_sym_Bin:Nn#1{\OrdSymbol{####1}}}}%
323 \def\math_sym_Rel:Nn#1##2{\gdef\binrel@@###1{\math_sym_Rel:Nn#1{\OrdSymbol{####1}}}}%
324 \def\math_sym_Pun:Nn#1##2{\gdef\binrel@@###1{\math_sym_Pun:Nn#1{\OrdSymbol{####1}}}}%
325 }
326 \def\binrel@#1{%
327 \setbox\z@\hbox{${}%
328 \let\mathchoice\@gobblethree
329 \let\@sym\binrel@sym \binrel@a
330 #1$}%
331 }
332 \def\@symextension{sym}
333 \newcommand\usesymbols[1]{%
334 \clist_map_variable:nN{#1}\@tempb{%
335 \exp_args:No\@onefilewithoptions{\@tempb}[] []\@symextension
336 }%
337 }
338 % Need to introduce \ProvidesExplFile somehow
339 \newcommand\ProvidesSymbols[1]{\ProvidesFile{#1.sym}}
340 \DeclareRobustCommand{\not}[1]{\math_csym_Rel:Nn\not{\OrdSymbol{\notRel#1}}}
341 \DeclareRobustCommand{\OrdSymbol}[1]{%
342 \begingroup\mathchars@reset#1\endgroup
343 }
344 \def\mathchars@reset{\let\@sym\@sym@ord \let\@symtype\@symtype@ord
345 \let\OrdSymbol\relax}
346 \def\@symtype@ord#1#2{\@symtype@ord#1#2}% a strange sort of \@gobble
347 \def\@sym@ord#1#2{\exp_after:wN\@sym@ord@a\string#2\@nil}%

Read delimited argument here. We want to find first character of DeA, Bin, etc.
and the control sequence checked against is \m@DeL, \m@Pun, etc. The lccode trick
makes the . into an @ with catcode 12. This is what results when the code is
called with \string. Beware of this when we change internal names for math
groups! If a Delimiter is found, insert it with class 0 but use the smallest version
available. Otherwise just insert math char of class 0. The code here is not pretty
and it indicates it should be tackled differently!

348 \begingroup
349 \lccode'\.='\_ \lowercase{\endgroup
350 \def\@sym@ord@a#1.#2.}#3#4\@nil#5#6{%
351 \if D#3
352 %\math_ord_delim_aux:Nn #5{#6}

```

```

353     \math_sd_del_aux:Nnn 0 #5{#6}% check if this works!
354   \else
355     \math_char:NNn 0 #5{#6}
356   \fi
357 }
358 \cs_set:Nn \math_ord_delim_aux:Nn {
359   \math_sd_aux:nn { \math_char:NNn 0 } {#1{#2}}
360 }

```

Before declaring any math characters active, we have to take care of a small problem with `amsmath v2.x`, if it is loaded before `flexisym`. `\std@minus` and `\std@equal` are defined as

```

\mathchardef\std@minus\mathcode'\- \relax
\mathchardef\std@equal\mathcode'\= \relax

```

in `amsmath.sty` and again `\AtBeginDocument`. The latter is because

In case some alternative math fonts are loaded later. [`amsmath.dtx`]

The problem arises because `flexisym` sets the mathcode of all symbols to 32768 which is illegal for a `\mathchardef`.

We have to remove the assignments from the `\AtBeginDocument` hook as they will cause an error there.

```

361 \ifpackageloaded{amsmath}{%
362   \begingroup

```

Split the contents of `\@begindocumenthook` by reading what we search for as a delimited argument and ensure these two assignments do not take place. It is questionable if anything reasonable can be done to them. In the case of a package such as `mathpazo` which defines

```

\DeclareMathSymbol{=}{\mathrel}{upright}{"3D}

```

the `\Relbar` will look wrong if we don't use the correct symbol. The way to solve this is define additional `.sym` files which contain the definition of `\relbar` and `\Relbar` needed. We need those additional files anyway for things like `\joinord`.

```

363   \long\def\next#1\mathchardef\std@minus\mathcode'\- \relax
364     \mathchardef\std@equal\mathcode'\= \relax#2\flexi@stop{%
365     \toks@{#1#2}%
366     \xdef\@begindocumenthook{\the\toks@}%
367   }%
368   \expandafter\next\@begindocumenthook\flexi@stop
369   \endgroup
370 }{}

```

There is problem when using `\DeclareMathOperator` as the operators defined call a command `\newmcodes@` which relies on the mathcode of `-` being less than 32768. We delay the definition `\AtBeginDocument` in case `amssymb` hasn't been loaded yet.

```

371 \AtBeginDocument{%
372 \def\newmcodes@{%
373   \mathcode '\ '39\space
374   \mathcode '\*42\space
375   \mathcode '\."613A\space
376   \ifnum\mathcode'\-=45\space
377   \else

```

The extra check. Don't do anything if - is math active.

```

378     \ifnum\mathcode'\-=32768\space
379     \else
380       \mathchardef \std@minus \mathcode '\-\relax
381     \fi
382   \fi
383   \mathcode '\-45\space
384   \mathcode '\ /47\space
385   \mathcode '\:"603A\space\relax
386 }%
387 }

```

And we then continue with the options.

```

388 \DeclareOption{mathstyleoff}{%
389   \PassOptionsToPackage{noactivechars}{mathstyle}}
390 \DeclareOption{cmbase}{\usesymbols{cmbase}}
391 \DeclareOption{mathpazo}{\usesymbols{mathpazo}}
392 \DeclareOption{mathptmx}{\usesymbols{mathptmx}}
393 \ExecuteOptions{cmbase}
394 \ProcessOptions\relax
395 \renewcommand{\lnot}{\neg}
396 \renewcommand{\land}{\wedge}
397 \renewcommand{\lor}{\vee}
398 \renewcommand{\le}{\leq}
399 \renewcommand{\ge}{\geq}
400 \renewcommand{\ne}{\neq}
401 \renewcommand{\owns}{\ni}
402 \renewcommand{\gets}{\leftarrow}
403 \renewcommand{\to}{\rightarrow}
404 \renewcommand{\|}{\Vert}
405 \RequirePackage{mathstyle}
406 \endinput

```

## 2 cmbase, mathpazo, mathptmx

For each math font package we define a corresponding symbol file with extension `sym`. The Computer Modern base is called `cmbase` and `mathpazo` and `mathptmx` corresponds to the packages. The definitions are almost identical as they mostly concern the positions in the math font encodings. Look for differences in `\joinord`, `\relbar` and `\Relbar`. If you inspect the source code, you'll see that the support

for mathptmx didn't require any work but I thought it better to create a `sym` file to maintain a uniform interface.

**Open question on ! and ?: maybe they should have type 'Pun' instead of 'DeR'. Need to search for uses in math in AMS archives. Or, maybe add a special 'Clo' type for them: non-extensible closing delimiter.**

Default mathgroup setup.

```

407 <*cmbase | mathpazo | mathptmx>
408 <cmbase> \ProvidesSymbols{cmbase}[2007/12/19 v0.92]
409 <mathpazo> \ProvidesSymbols{mathpazo}[2010/07/11 v0.3]
410 <mathptmx> \ProvidesSymbols{mathptmx}[2010/07/11 v0.3]
411 \ExplSyntaxOn
412 \cs_gset:cpx {mg@OT1} {\hexnumber@\symoperators}
413 \cs_gset:cpx {mg@OML} {\hexnumber@\symletters}
414 \cs_gset:cpx {mg@OMS} {\hexnumber@\symsymbols}
415 \cs_gset:cpx {mg@OMX} {\hexnumber@\symlargesymbols}
416 \cs_gset:Npx \mg@bin {\mg@OMS}
417 \cs_gset:Npx \mg@del {\mg@OMX}
418 \cs_gset:Npx \mg@digit {\exp_not:c{mg@OT1}}
419 \cs_gset:Npn \mg@latin {\mg@OML}
420 \cs_gset_eq:NN \mg@Latin \mg@latin
421 \cs_gset_eq:NN \mg@greek \mg@latin
422 <cmbase | mathptmx> \cs_gset_eq:NN \mg@greek \mg@digit

```

Mathpazo takes the upper case greeks from the letter font if `slantedGreek` is in effect, but from *upright* if not. Mathptmx also takes the slanted greek from the letter font.

```

423 <mathpazo> \@ifpackagewith{mathpazo}{slantedGreek}{%
424 <mathpazo> \cs_gset_eq:NN \mg@greek \mg@latin
425 <mathpazo> }{%
426 <mathpazo> \cs_gset:cpx {mg@greek} {\hexnumber@\symupright}
427 <mathpazo> }
428 <mathptmx> \@ifpackagewith{mathptmx}{slantedGreek}{%
429 <mathptmx> \cs_gset_eq:NN \mg@greek \mg@latin
430 <mathptmx> }{}
431 \cs_gset_eq:NN \mg@rel \mg@bin
432 \cs_gset_eq:NN \mg@ord \mg@bin
433 \cs_gset_eq:NN \mg@cop \mg@del

```

Symbols from the 128-character `cmr` encoding. Paren and square bracket delimiters from this encoding are covered by the definitions in the `cmex` section, however.

```

434 \DeclareFlexSymbol{!} {\Pun}{OT1}{21}
435 \DeclareFlexSymbol{+} {\Bin}{OT1}{2B}
436 \DeclareFlexSymbol{:} {\Rel}{OT1}{3A}
437 \DeclareFlexSymbol{colon} {\Pun}{OT1}{3A}
438 \DeclareFlexSymbol{;} {\Pun}{OT1}{3B}
439 \DeclareFlexSymbol{=} {\Rel}{OT1}{3D}

```

```
440 \DeclareFlexSymbol{?}      {Pun}{OT1}{3F}
```

$\mathcal{A}\mathcal{M}\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ , and therefore the `amsmath` package, make the uppercase Greek letters class 0 (nonvariable) instead of 7 (variable), to eliminate the glaring inconsistency with lowercase Greek. (In plain  $\mathcal{T}\mathcal{E}\mathcal{X}$ , `{\bf\Delta}` works, while `{\bf\delta}` doesn't.) Let us try to make them both variable (fonts permitting) instead of nonvariable.

```
441 \DeclareFlexSymbol{\Gamma}  {Var}{Greek}{00}
442 \DeclareFlexSymbol{\Delta}  {Var}{Greek}{01}
443 \DeclareFlexSymbol{\Theta}  {Var}{Greek}{02}
444 \DeclareFlexSymbol{\Lambda} {Var}{Greek}{03}
445 \DeclareFlexSymbol{\Xi}     {Var}{Greek}{04}
446 \DeclareFlexSymbol{\Pi}     {Var}{Greek}{05}
447 \DeclareFlexSymbol{\Sigma}  {Var}{Greek}{06}
448 \DeclareFlexSymbol{\Upsilon}{Var}{Greek}{07}
449 \DeclareFlexSymbol{\Phi}    {Var}{Greek}{08}
450 \DeclareFlexSymbol{\Psi}    {Var}{Greek}{09}
451 \DeclareFlexSymbol{\Omega}  {Var}{Greek}{0A}
```

Decimal digits.

```
452 \DeclareFlexSymbol{0}{Var}{digit}{30}
453 \DeclareFlexSymbol{1}{Var}{digit}{31}
454 \DeclareFlexSymbol{2}{Var}{digit}{32}
455 \DeclareFlexSymbol{3}{Var}{digit}{33}
456 \DeclareFlexSymbol{4}{Var}{digit}{34}
457 \DeclareFlexSymbol{5}{Var}{digit}{35}
458 \DeclareFlexSymbol{6}{Var}{digit}{36}
459 \DeclareFlexSymbol{7}{Var}{digit}{37}
460 \DeclareFlexSymbol{8}{Var}{digit}{38}
461 \DeclareFlexSymbol{9}{Var}{digit}{39}
```

Symbols from the 128-character `cmmi` encoding.

```
462 \DeclareFlexSymbol{,}{Pun}{OML}{3B}
463 \DeclareFlexSymbol{.}{Ord}{OML}{3A}
464 \DeclareFlexSymbol{/}{Ord}{OML}{3D}
465 \DeclareFlexSymbol{<}{Rel}{OML}{3C}
466 \DeclareFlexSymbol{>}{Rel}{OML}{3E}
```

To do: make the `Var` property of `lc Greek` work properly.

```
467 \DeclareFlexSymbol{\alpha}  {Var}{greek}{0B}
468 \DeclareFlexSymbol{\beta}   {Var}{greek}{0C}
469 \DeclareFlexSymbol{\gamma}  {Var}{greek}{0D}
470 \DeclareFlexSymbol{\delta}  {Var}{greek}{0E}
471 \DeclareFlexSymbol{\epsilon}{Var}{greek}{0F}
472 \DeclareFlexSymbol{\zeta}   {Var}{greek}{10}
473 \DeclareFlexSymbol{\eta}     {Var}{greek}{11}
474 \DeclareFlexSymbol{\theta}  {Var}{greek}{12}
475 \DeclareFlexSymbol{\iota}   {Var}{greek}{13}
476 \DeclareFlexSymbol{\kappa}  {Var}{greek}{14}
477 \DeclareFlexSymbol{\lambda} {Var}{greek}{15}
478 \DeclareFlexSymbol{\mu}     {Var}{greek}{16}
```

```

479 \DeclareFlexSymbol{\nu}          {Var}{greek}{17}
480 \DeclareFlexSymbol{\xi}          {Var}{greek}{18}
481 \DeclareFlexSymbol{\pi}          {Var}{greek}{19}
482 \DeclareFlexSymbol{\rho}         {Var}{greek}{1A}
483 \DeclareFlexSymbol{\sigma}       {Var}{greek}{1B}
484 \DeclareFlexSymbol{\tau}         {Var}{greek}{1C}
485 \DeclareFlexSymbol{\upsilon}     {Var}{greek}{1D}
486 \DeclareFlexSymbol{\phi}         {Var}{greek}{1E}
487 \DeclareFlexSymbol{\chi}         {Var}{greek}{1F}
488 \DeclareFlexSymbol{\psi}         {Var}{greek}{20}
489 \DeclareFlexSymbol{\omega}       {Var}{greek}{21}
490 \DeclareFlexSymbol{\varepsilon}  {Var}{greek}{22}
491 \DeclareFlexSymbol{\vartheta}    {Var}{greek}{23}
492 \DeclareFlexSymbol{\varpi}       {Var}{greek}{24}
493 \DeclareFlexSymbol{\varrho}      {Var}{greek}{25}
494 \DeclareFlexSymbol{\varsigma}    {Var}{greek}{26}
495 \DeclareFlexSymbol{\varphi}      {Var}{greek}{27}

```

Note that in plain TeX `\imath` and `\jmath` are not variable-font. But if a `j` changes font to, let's say, sans serif or calligraphic, a dotless `j` in the same context should change font in the same way.

```

496 \DeclareFlexSymbol{\imath}       {Var}{OML}{7B}
497 \DeclareFlexSymbol{\jmath}       {Var}{OML}{7C}
498 \DeclareFlexSymbol{\ell}         {Ord}{OML}{60}
499 \DeclareFlexSymbol{\wp}          {Ord}{OML}{7D}
500 \DeclareFlexSymbol{\partial}      {Ord}{OML}{40}
501 \DeclareFlexSymbol{\flat}        {Ord}{OML}{5B}
502 \DeclareFlexSymbol{\natural}     {Ord}{OML}{5C}
503 \DeclareFlexSymbol{\sharp}       {Ord}{OML}{5D}
504 \DeclareFlexSymbol{\triangleleft} {Bin}{OML}{2F}
505 \DeclareFlexSymbol{\triangleright} {Bin}{OML}{2E}
506 \DeclareFlexSymbol{\star}        {Bin}{OML}{3F}
507 \DeclareFlexSymbol{\smile}       {Rel}{OML}{5E}
508 \DeclareFlexSymbol{\frown}       {Rel}{OML}{5F}
509 \DeclareFlexSymbol{\leftharpoonup} {Rel}{OML}{28}
510 \DeclareFlexSymbol{\leftharpoondown} {Rel}{OML}{29}
511 \DeclareFlexSymbol{\rightharpoonup} {Rel}{OML}{2A}
512 \DeclareFlexSymbol{\rightharpoondown} {Rel}{OML}{2B}

```

Latin

```

513 \DeclareFlexSymbol{a}{Var}{latin}{61}
514 \DeclareFlexSymbol{b}{Var}{latin}{62}
515 \DeclareFlexSymbol{c}{Var}{latin}{63}
516 \DeclareFlexSymbol{d}{Var}{latin}{64}
517 \DeclareFlexSymbol{e}{Var}{latin}{65}
518 \DeclareFlexSymbol{f}{Var}{latin}{66}
519 \DeclareFlexSymbol{g}{Var}{latin}{67}
520 \DeclareFlexSymbol{h}{Var}{latin}{68}
521 \DeclareFlexSymbol{i}{Var}{latin}{69}
522 \DeclareFlexSymbol{j}{Var}{latin}{6A}

```

```

523 \DeclareFlexSymbol{k}{Var}{latin}{6B}
524 \DeclareFlexSymbol{l}{Var}{latin}{6C}
525 \DeclareFlexSymbol{m}{Var}{latin}{6D}
526 \DeclareFlexSymbol{n}{Var}{latin}{6E}
527 \DeclareFlexSymbol{o}{Var}{latin}{6F}
528 \DeclareFlexSymbol{p}{Var}{latin}{70}
529 \DeclareFlexSymbol{q}{Var}{latin}{71}
530 \DeclareFlexSymbol{r}{Var}{latin}{72}
531 \DeclareFlexSymbol{s}{Var}{latin}{73}
532 \DeclareFlexSymbol{t}{Var}{latin}{74}
533 \DeclareFlexSymbol{u}{Var}{latin}{75}
534 \DeclareFlexSymbol{v}{Var}{latin}{76}
535 \DeclareFlexSymbol{w}{Var}{latin}{77}
536 \DeclareFlexSymbol{x}{Var}{latin}{78}
537 \DeclareFlexSymbol{y}{Var}{latin}{79}
538 \DeclareFlexSymbol{z}{Var}{latin}{7A}
539 \DeclareFlexSymbol{A}{Var}{Latin}{41}
540 \DeclareFlexSymbol{B}{Var}{Latin}{42}
541 \DeclareFlexSymbol{C}{Var}{Latin}{43}
542 \DeclareFlexSymbol{D}{Var}{Latin}{44}
543 \DeclareFlexSymbol{E}{Var}{Latin}{45}
544 \DeclareFlexSymbol{F}{Var}{Latin}{46}
545 \DeclareFlexSymbol{G}{Var}{Latin}{47}
546 \DeclareFlexSymbol{H}{Var}{Latin}{48}
547 \DeclareFlexSymbol{I}{Var}{Latin}{49}
548 \DeclareFlexSymbol{J}{Var}{Latin}{4A}
549 \DeclareFlexSymbol{K}{Var}{Latin}{4B}
550 \DeclareFlexSymbol{L}{Var}{Latin}{4C}
551 \DeclareFlexSymbol{M}{Var}{Latin}{4D}
552 \DeclareFlexSymbol{N}{Var}{Latin}{4E}
553 \DeclareFlexSymbol{O}{Var}{Latin}{4F}
554 \DeclareFlexSymbol{P}{Var}{Latin}{50}
555 \DeclareFlexSymbol{Q}{Var}{Latin}{51}
556 \DeclareFlexSymbol{R}{Var}{Latin}{52}
557 \DeclareFlexSymbol{S}{Var}{Latin}{53}
558 \DeclareFlexSymbol{T}{Var}{Latin}{54}
559 \DeclareFlexSymbol{U}{Var}{Latin}{55}
560 \DeclareFlexSymbol{V}{Var}{Latin}{56}
561 \DeclareFlexSymbol{W}{Var}{Latin}{57}
562 \DeclareFlexSymbol{X}{Var}{Latin}{58}
563 \DeclareFlexSymbol{Y}{Var}{Latin}{59}
564 \DeclareFlexSymbol{Z}{Var}{Latin}{5A}

```

The `\ldotPun` glyph is used in constructing the `\ldots` symbol. It is just a period with a different math symbol class. `\lhookRel` and `\rhookRel` are used in a similar way for building hooked arrow symbols.

```

565 \DeclareFlexSymbol{\ldotPun}{Pun}{OML}{3A}
566 \def\ldotp{\ldotPun}
567 \DeclareFlexSymbol{\lhookRel}{Rel}{OML}{2C}
568 \DeclareFlexSymbol{\rhookRel}{Rel}{OML}{2D}

```



Symbols from the 128-character cmsy encoding.

```

569 \DeclareFlexSymbol{*}           {Bin}{bin}{03} % \ast
570 \DeclareFlexSymbol{-}          {Bin}{bin}{00}
571 \DeclareFlexSymbol{|}           {Ord}{ord}{6A}
572 \DeclareFlexSymbol{\aleph}      {Ord}{ord}{40}
573 \DeclareFlexSymbol{\Re}         {Ord}{ord}{3C}
574 \DeclareFlexSymbol{\Im}         {Ord}{ord}{3D}
575 \DeclareFlexSymbol{\infty}      {Ord}{ord}{31}
576 \DeclareFlexSymbol{\prime}      {Ord}{ord}{30}
577 \DeclareFlexSymbol{\emptyset}   {Ord}{ord}{3B}
578 \DeclareFlexSymbol{\nabla}      {Ord}{ord}{72}
579 \DeclareFlexSymbol{\top}        {Ord}{ord}{3E}
580 \DeclareFlexSymbol{\bot}        {Ord}{ord}{3F}
581 \DeclareFlexSymbol{\triangle}   {Ord}{ord}{34}
582 \DeclareFlexSymbol{\forall}     {Ord}{ord}{38}
583 \DeclareFlexSymbol{\exists}     {Ord}{ord}{39}
584 \DeclareFlexSymbol{\neg}        {Ord}{ord}{3A}
585 \DeclareFlexSymbol{\clubsuit}   {Ord}{ord}{7C}
586 \DeclareFlexSymbol{\diamondsuit}{Ord}{ord}{7D}
587 \DeclareFlexSymbol{\heartsuit}  {Ord}{ord}{7E}
588 \DeclareFlexSymbol{\spadesuit}  {Ord}{ord}{7F}
589 \DeclareFlexSymbol{\smallint}   {COs}{OMS}{73}

```

Binary operators.

```

590 \DeclareFlexSymbol{\bigtriangleup} {Bin}{bin}{34}
591 \DeclareFlexSymbol{\bigtriangledown}{Bin}{bin}{35}
592 \DeclareFlexSymbol{\wedge}         {Bin}{bin}{5E}
593 \DeclareFlexSymbol{\vee}          {Bin}{bin}{5F}
594 \DeclareFlexSymbol{\cap}           {Bin}{bin}{5C}
595 \DeclareFlexSymbol{\cup}           {Bin}{bin}{5B}
596 \DeclareFlexSymbol{\ddagger}      {Bin}{bin}{7A}
597 \DeclareFlexSymbol{\dagger}       {Bin}{bin}{79}
598 \DeclareFlexSymbol{\sqcap}        {Bin}{bin}{75}
599 \DeclareFlexSymbol{\sqcup}        {Bin}{bin}{74}
600 \DeclareFlexSymbol{\uplus}        {Bin}{bin}{5D}
601 \DeclareFlexSymbol{\amalg}        {Bin}{bin}{71}
602 \DeclareFlexSymbol{\diamond}      {Bin}{bin}{05}
603 \DeclareFlexSymbol{\bullet}       {Bin}{bin}{0F}
604 \DeclareFlexSymbol{\wr}           {Bin}{bin}{6F}
605 \DeclareFlexSymbol{\div}           {Bin}{bin}{04}
606 \DeclareFlexSymbol{\odot}         {Bin}{bin}{0C}
607 \DeclareFlexSymbol{\oslash}       {Bin}{bin}{0B}
608 \DeclareFlexSymbol{\otimes}       {Bin}{bin}{0A}
609 \DeclareFlexSymbol{\ominus}       {Bin}{bin}{09}
610 \DeclareFlexSymbol{\oplus}        {Bin}{bin}{08}
611 \DeclareFlexSymbol{\mp}           {Bin}{bin}{07}
612 \DeclareFlexSymbol{\pm}           {Bin}{bin}{06}
613 \DeclareFlexSymbol{\circ}         {Bin}{bin}{0E}
614 \DeclareFlexSymbol{\bigcirc}      {Bin}{bin}{0D}
615 \DeclareFlexSymbol{\setminus}     {Bin}{bin}{6E}

```

|     |   |                             |
|-----|---|-----------------------------|
| 616 | <code>\DeclareFlexSymbol{\cdot}</code>  | <code>{Bin}{bin}{01}</code> |
| 617 | <code>\DeclareFlexSymbol{\ast}</code>   | <code>{Bin}{bin}{03}</code> |
| 618 | <code>\DeclareFlexSymbol{\times}</code> | <code>{Bin}{bin}{02}</code> |

Relation symbols.

|     |  |                             |
|-----|--|-----------------------------|
| 619 | <code>\DeclareFlexSymbol{\propto}</code>             | <code>{Rel}{rel}{2F}</code> |
| 620 | <code>\DeclareFlexSymbol{\sqsubseteq}</code>         | <code>{Rel}{rel}{76}</code> |
| 621 | <code>\DeclareFlexSymbol{\sqsupseteq}</code>         | <code>{Rel}{rel}{77}</code> |
| 622 | <code>\DeclareFlexSymbol{\parallel}</code>           | <code>{Rel}{rel}{6B}</code> |
| 623 | <code>\DeclareFlexSymbol{\mid}</code>                | <code>{Rel}{rel}{6A}</code> |
| 624 | <code>\DeclareFlexSymbol{\dashv}</code>              | <code>{Rel}{rel}{61}</code> |
| 625 | <code>\DeclareFlexSymbol{\vdash}</code>              | <code>{Rel}{rel}{60}</code> |
| 626 | <code>\DeclareFlexSymbol{\nearrow}</code>            | <code>{Rel}{rel}{25}</code> |
| 627 | <code>\DeclareFlexSymbol{\searrow}</code>            | <code>{Rel}{rel}{26}</code> |
| 628 | <code>\DeclareFlexSymbol{\nwarrow}</code>            | <code>{Rel}{rel}{2D}</code> |
| 629 | <code>\DeclareFlexSymbol{\swarrow}</code>            | <code>{Rel}{rel}{2E}</code> |
| 630 | <code>\DeclareFlexSymbol{\Leftrightarrow}</code>     | <code>{Rel}{rel}{2C}</code> |
| 631 | <code>\DeclareFlexSymbol{\Leftarrow}</code>          | <code>{Rel}{rel}{28}</code> |
| 632 | <code>\DeclareFlexSymbol{\Rightarrow}</code>         | <code>{Rel}{rel}{29}</code> |
| 633 | <code>\DeclareFlexSymbol{\leq}</code>                | <code>{Rel}{rel}{14}</code> |
| 634 | <code>\DeclareFlexSymbol{\geq}</code>                | <code>{Rel}{rel}{15}</code> |
| 635 | <code>\DeclareFlexSymbol{\succ}</code>               | <code>{Rel}{rel}{1F}</code> |
| 636 | <code>\DeclareFlexSymbol{\prec}</code>               | <code>{Rel}{rel}{1E}</code> |
| 637 | <code>\DeclareFlexSymbol{\approx}</code>             | <code>{Rel}{rel}{19}</code> |
| 638 | <code>\DeclareFlexSymbol{\succeq}</code>             | <code>{Rel}{rel}{17}</code> |
| 639 | <code>\DeclareFlexSymbol{\preceq}</code>             | <code>{Rel}{rel}{16}</code> |
| 640 | <code>\DeclareFlexSymbol{\supseteq}</code>           | <code>{Rel}{rel}{1B}</code> |
| 641 | <code>\DeclareFlexSymbol{\subseteq}</code>           | <code>{Rel}{rel}{1A}</code> |
| 642 | <code>\DeclareFlexSymbol{\supseteqeq}</code>         | <code>{Rel}{rel}{13}</code> |
| 643 | <code>\DeclareFlexSymbol{\subseteqeq}</code>         | <code>{Rel}{rel}{12}</code> |
| 644 | <code>\DeclareFlexSymbol{\in}</code>                 | <code>{Rel}{rel}{32}</code> |
| 645 | <code>\DeclareFlexSymbol{\ni}</code>                 | <code>{Rel}{rel}{33}</code> |
| 646 | <code>\DeclareFlexSymbol{\gg}</code>                 | <code>{Rel}{rel}{1D}</code> |
| 647 | <code>\DeclareFlexSymbol{\ll}</code>                 | <code>{Rel}{rel}{1C}</code> |
| 648 | <code>\DeclareFlexSymbol{\leftrightharpoonup}</code> | <code>{Rel}{rel}{24}</code> |
| 649 | <code>\DeclareFlexSymbol{\leftarrow}</code>          | <code>{Rel}{rel}{20}</code> |
| 650 | <code>\DeclareFlexSymbol{\rightarrow}</code>         | <code>{Rel}{rel}{21}</code> |
| 651 | <code>\DeclareFlexSymbol{\sim}</code>                | <code>{Rel}{rel}{18}</code> |
| 652 | <code>\DeclareFlexSymbol{\simeq}</code>              | <code>{Rel}{rel}{27}</code> |
| 653 | <code>\DeclareFlexSymbol{\perp}</code>               | <code>{Rel}{rel}{3F}</code> |
| 654 | <code>\DeclareFlexSymbol{\equiv}</code>              | <code>{Rel}{rel}{11}</code> |
| 655 | <code>\DeclareFlexSymbol{\asymp}</code>              | <code>{Rel}{rel}{10}</code> |

The `\notRel` glyph is a special zero-width glyph intended only for use in constructing negated symbols. `\mapstoRel` and `\cdotPun` have similar but more restricted applications.

|     |  |                             |
|-----|--|-----------------------------|
| 656 | <code>\DeclareFlexSymbol{\notRel}</code>             | <code>{Rel}{rel}{36}</code> |
| 657 | <code>\DeclareFlexSymbol{\mapstoOrd}</code>          | <code>{Ord}{OMS}{37}</code> |
| 658 | <code>\DeclareFlexSymbol{\cdotOrd}</code>            | <code>{Ord}{OMS}{01}</code> |
| 659 | <code>\cs_set:Npn\cdotp{\mathpunct{\cdotOrd}}</code> |                             |

Symbols from the 128-character `cmex` encoding. `C0s` stands for ‘cumulative operator (sum-like)’. `C0i` stands for ‘cumulative operator (integral-like)’. These typically differ only in the default placement of limits. `cop` stands for ‘cumulative operator math group’.

```

660 \DeclareFlexSymbol{\coprod} {C0s}{cop}{60}
661 \DeclareFlexSymbol{\bigvee} {C0s}{cop}{57}
662 \DeclareFlexSymbol{\bigwedge} {C0s}{cop}{56}
663 \DeclareFlexSymbol{\biguplus} {C0s}{cop}{55}
664 \DeclareFlexSymbol{\bigcap} {C0s}{cop}{54}
665 \DeclareFlexSymbol{\bigcup} {C0s}{cop}{53}
666 \DeclareFlexSymbol{\int} {C0i}{cop}{52}
667 \DeclareFlexSymbol{\prod} {C0s}{cop}{51}
668 \DeclareFlexSymbol{\sum} {C0s}{cop}{50}
669 \DeclareFlexSymbol{\bigotimes} {C0s}{cop}{4E}
670 \DeclareFlexSymbol{\bigoplus} {C0s}{cop}{4C}
671 \DeclareFlexSymbol{\bigodot} {C0s}{cop}{4A}
672 \DeclareFlexSymbol{\oint} {C0i}{cop}{48}
673 \DeclareFlexSymbol{\bigsqcup} {C0s}{cop}{46}

```

Delimiter symbols. `DeL` stands for ‘delimiter (left)’. `DeR` stands for ‘delimiter (right)’. `DeB` stands for ‘delimiter (bidirectional)’. The principal encoding point for an extensible delimiter is the first link in the list of linked sizes as specified in the font metric information. For a math encoding such as OT1/OML/OMS/OMX where not all sizes of a given delimiter reside in a given font, the extra encoding point for the smallest delimiter must be supplied by defining

```
\sd@GXX
```

where `G` is the mathgroup and `XX` is the hexadecimal glyph position. `\DeclareFlexDelimiter` does that for us.

```

674 \DeclareFlexDelimiter{\rangle}{DeR}{del}{0B}{OMS}{69}
675 \DeclareFlexDelimiter{\langle}{DeL}{del}{0A}{OMS}{68}
676 \DeclareFlexDelimiter{\rbrace}{DeR}{del}{09}{OMS}{67}
677 \DeclareFlexDelimiter{\lbrace}{DeL}{del}{08}{OMS}{66}
678 \DeclareFlexDelimiter{\rceil} {DeR}{del}{07}{OMS}{65}
679 \DeclareFlexDelimiter{\lceil} {DeL}{del}{06}{OMS}{64}
680 \DeclareFlexDelimiter{\rfloor}{DeR}{del}{05}{OMS}{63}
681 \DeclareFlexDelimiter{\lfloor}{DeL}{del}{04}{OMS}{62}
682 \DeclareFlexDelimiter{()} {DeL}{del}{00}{OT1}{28}
683 \DeclareFlexDelimiter{)} {DeR}{del}{01}{OT1}{29}
684 \DeclareFlexDelimiter{[]} {DeL}{del}{02}{OT1}{5B}
685 \DeclareFlexDelimiter{[]}] {DeR}{del}{03}{OT1}{5D}
686 \DeclareFlexDelimiter{\lVert} {DeL}{del}{0D}{OMS}{6B}
687 \DeclareFlexDelimiter{\rVert} {DeR}{del}{0D}{OMS}{6B}
688 \DeclareFlexDelimiter{\lvert} {DeL}{del}{0C}{OMS}{6A}
689 \DeclareFlexDelimiter{\rvert} {DeR}{del}{0C}{OMS}{6A}
690 \DeclareFlexDelimiter{\Vert} {DeB}{del}{0D}{OMS}{6B}
691 \DeclareFlexDelimiter{\vert} {DeB}{del}{0C}{OMS}{6A}

```

Maybe make the vert bars mathord instead of delimiter, to discourage poor usage.

```
692 \DeclareFlexDelimiter{|}{DeB}{del}{0C}{OMS}{6A}
693 \DeclareFlexDelimiter{/}{DeB}{del}{0E}{OML}{3D}
```

These wacky delimiters need to be supported I guess for compabitility reasons.  
The DeA delimiter type is a special case used only for these arrows.

```
694 \DeclareFlexDelimiter{\lmoustache} {DeL}{del}{40}{del}{7A}
695 \DeclareFlexDelimiter{\rmoustache} {DeR}{del}{41}{del}{7B}
696 \DeclareFlexDelimiter{\lgroup} {DeL}{del}{3A}{del}{3A}
697 \DeclareFlexDelimiter{\rgroup} {DeR}{del}{3B}{del}{3B}
698 \DeclareFlexDelimiter{\bracevert} {DeB}{del}{3E}{del}{3E}
699 \DeclareFlexDelimiter{\arrowvert} {DeB}{del}{3C}{OMS}{6A}
700 \DeclareFlexDelimiter{\Arrowvert} {DeB}{del}{3D}{OMS}{6B}
701 \DeclareFlexDelimiter{\uparrow} {DeA}{del}{78}{OMS}{22}
702 \DeclareFlexDelimiter{\downarrow} {DeA}{del}{79}{OMS}{23}
703 \DeclareFlexDelimiter{\updownarrow} {DeA}{del}{3F}{OMS}{6C}
704 \DeclareFlexDelimiter{\Uparrow} {DeA}{del}{7E}{OMS}{2A}
705 \DeclareFlexDelimiter{\Downarrow} {DeA}{del}{7F}{OMS}{2B}
706 \DeclareFlexDelimiter{\Updownarrow} {DeA}{del}{77}{OMS}{6D}
707 \DeclareFlexDelimiter{\backslash} {DeB}{del}{0F}{OMS}{6E}
```

### 3 Some compound symbols

The following symbols are not robust in standard L<sup>A</sup>T<sub>E</sub>X because they use # or \mathpalette (which is not robust and contains a # in its expansion): \angle, \cong, \notin, \rightleftharpoons.

In this definition of \hbar, the symbol is cobbled together from a math italic h and the cmr overbar accent glyph.

```
708 \DeclareFlexSymbol{\hbarOrd}{Ord}{OT1}{16}
709 \DeclareFlexCompoundSymbol{\hbar}{Ord}{\hbarOrd\mkern-9mu h}
```

For \surd, the interior symbol gets math class 1 (cumulative operator) to make the glyph vertically centered on the math axis, but the desired horizontal spacing is the spacing for a mathord. (Couldn't it just be class mathopen, though?)

```
710 \DeclareFlexSymbol{\surdOrd}{Ord}{OMS}{70}
711 \DeclareFlexCompoundSymbol{\surd}{Ord}{\mathop{\surdOrd}}
```

As shown in this definition of \angle, rule dimens are not allowed to use math-units, unfortunately.

```
712 \DeclareFlexCompoundSymbol{\angle}{Ord}{%
713   \vbox{\ialign{%
714     $m@th\scriptstyle##$\cr
715     \notRel\mathrel{\mkern14mu}\cr
716     \noalign{\nointerlineskip}%
717     \mkern2.5mu\leaders\hrule \@height.34pt\hfill\mkern2.5mu\cr
718   }}%
719 }
```

The `\not` function, which is defined in the `flexisym` package, requires a suitably defined `\notRel` symbol.

```
720 \DeclareFlexCompoundSymbol{\neq}{Rel}{\not{=}}
```

.

```
721 \DeclareFlexCompoundSymbol{\mapsto}{Rel}{\mapstoOrd\rightarrow}
```

The `\@vereq` function ends by centering the whole construction on the math axis, unlike `\buildrel` where the base symbol remains at its normal altitude. Furthermore, `\@vereq` leaves the math style of the top symbol as given instead of downsizing to `scriptstyle`.

```
722 \DeclareFlexCompoundSymbol{\cong}{Rel}{\mathpalette\@vereq\sim}
```

The `\m@th` in the `fontmath.ltx` definition of `\notin` is superfluous unless `\c@ncel` doesn't include it (which was perhaps true in an older version of `plain.tex`).

```
723 \providecommand*\joinord{}
```

```
724 \cmbase | mathptmx \renewcommand*\joinord{\mkern-3mu }
```

```
725 \mathpazo \renewcommand*\joinord{\mkern-3.45mu }
```

```
726 \DeclareFlexCompoundSymbol{\notin}{Rel}{\mathpalette\c@ncel\in}
```

```
727 \DeclareFlexCompoundSymbol{\rightleftharpoons}{Rel}{\mathpalette\rlh@{}}
```

```
728 \DeclareFlexCompoundSymbol{\doteq}{Rel}{\buildrel\textstyle.\over=}
```

```
729 \DeclareFlexCompoundSymbol{\hookrightarrow}{Rel}{\lhookRel\joinord\rightarrow}
```

```
730 \DeclareFlexCompoundSymbol{\hookleftarrow}{Rel}{\leftarrow\joinord\rhookRel}
```

```
731 \DeclareFlexCompoundSymbol{\bowtie}{Rel}{\triangleright\joinord\triangleleft}
```

```
732 \DeclareFlexCompoundSymbol{\models}{Rel}{\vert\joinord=}
```

```
733 \DeclareFlexCompoundSymbol{\Longrightarrow}{Rel}{\Relbar\joinord\Rightarrow}
```

```
734 \DeclareFlexCompoundSymbol{\longrightarrow}{Rel}{\relbar\joinord\rightarrow}
```

```
735 \DeclareFlexCompoundSymbol{\Longleftarrow}{Rel}{\Leftarrow\joinord\Relbar}
```

```
736 \DeclareFlexCompoundSymbol{\longleftarrow}{Rel}{\leftarrow\joinord\relbar}
```

```
737 \DeclareFlexCompoundSymbol{\longmapsto}{Rel}{\mapstochar\longrightarrow}
```

```
738 \DeclareFlexCompoundSymbol{\longleftrightharrow}{Rel}{\leftarrow\joinord\rightarrow}
```

```
739 \DeclareFlexCompoundSymbol{\Longleftrightharrow}{Rel}{\Leftarrow\joinord\Rightarrow}
```

Here is what you get from the old definition of `\iff`.

```
\glue 2.77771 plus 2.77771
\glue(\thickmuskip) 2.77771 plus 2.77771
\OMS/cmsy/m/n/10 (
\hbox(0.0+0.0)x-1.66663
.\kern -1.66663
\OMS/cmsy/m/n/10 )
\penalty 500
\glue 2.77771 plus 2.77771
\glue(\thickmuskip) 2.77771 plus 2.77771
```

Looks like it could be simplified slightly. But it's not so easy as it looks to do it without screwing up the line breaking possibilities.

```
740 \renewcommand*\iff{%
```

```
741 \mskip\thickmuskip\Longleftrightharrow\mskip\thickmuskip
```

```
742 }
```

Some dotly symbols.

```

743 \DeclareFlexCompoundSymbol{\cdots}{Inn}{\cdotp\cdotp\cdotp}%
744 \DeclareFlexCompoundSymbol{\vdots}{Ord}{%
745   \vbox{\baselineskip4p@ \lineskiplimit\z@
746     \kern6p@\hbox{.}\hbox{.}\hbox{.}}}
747 \DeclareFlexCompoundSymbol{\ddots}{Inn}{%
748   \mkern1mu\raise7p@
749   \vbox{\kern7p@\hbox{.}}\mkern2mu%
750   \raise4p@\hbox{.}\mkern2mu\raise\p@\hbox{.}\mkern1mu%
751 }

```

```

.
752 \def\relbar{\begingroup \def\smash@{tb}% in case amsmath is loaded
753   \mathpalette\mathsm@sh{\mathchar"200 }\endgroup}

```

For `\Relbar` we take an equal sign of class 0 (Ord) from the operator family. For `cmr` and `mathptmx` we know this is family 0.

```

754 <cmr | mathptmx> \def\Relbar{\mathchar"3D }

```

For the `mathpazo` setup we need to use the equal sign from `cmr` and so must insert class 0 and use the symbol from the upright symbols.

```

755 <mathpazo> \edef\Relbar{\mathchar\string"hexnumber@\symupright3D }

```

Done.

```

756 \ExplSyntaxOff
757 </cmr | mathpazo | mathptmx>

```

Various synonyms such as `\le` for `\leq` and `\to` for `\rightarrow` are defined in `flexsym` with `\def` instead of `\let`, for slower execution speed but smaller chance of synchronization problems.

```

758 <*msabm>
759 \ProvidesSymbols{msabm}[2001/09/08 v0.91]
760 \ExplSyntaxOn
761 \RequirePackage{amsfonts}\relax
762 \cs_gset:cpx{mg@MSA}{\hexnumber@\symAMSa}%
763 \cs_gset:cpx{mg@MSB}{\hexnumber@\symAMSb}%

```

```

764 \DeclareFlexSymbol{\boxdot}          {Bin}{MSA}{00}
765 \DeclareFlexSymbol{\boxplus}         {Bin}{MSA}{01}
766 \DeclareFlexSymbol{\boxtimes}        {Bin}{MSA}{02}
767 \DeclareFlexSymbol{\square}          {Ord}{MSA}{03}
768 \DeclareFlexSymbol{\blacksquare}     {Ord}{MSA}{04}
769 \DeclareFlexSymbol{\centerdot}       {Bin}{MSA}{05}
770 \DeclareFlexSymbol{\lozenge}         {Ord}{MSA}{06}
771 \DeclareFlexSymbol{\blacklozenge}    {Ord}{MSA}{07}
772 \DeclareFlexSymbol{\circlearrowright}{Rel}{MSA}{08}
773 \DeclareFlexSymbol{\circlearrowleft}{Rel}{MSA}{09}

```

In `amsfonts.sty`:

```

774 %\DeclareFlexSymbol{\rightleftharpoons}{Rel}{MSA}{0A}
775 \DeclareFlexSymbol{\leftrightharpoons}{Rel}{MSA}{0B}

```

|     |   |                             |
|-----|---|-----------------------------|
| 776 | <code>\DeclareFlexSymbol{\boxminus}</code>            | <code>{Bin}{MSA}{0C}</code> |
| 777 | <code>\DeclareFlexSymbol{\Vdash}</code>               | <code>{Rel}{MSA}{0D}</code> |
| 778 | <code>\DeclareFlexSymbol{\Vvdash}</code>              | <code>{Rel}{MSA}{0E}</code> |
| 779 | <code>\DeclareFlexSymbol{\vDash}</code>               | <code>{Rel}{MSA}{0F}</code> |
| 780 | <code>\DeclareFlexSymbol{\twoheadrightarrow}</code>   | <code>{Rel}{MSA}{10}</code> |
| 781 | <code>\DeclareFlexSymbol{\twoheadleftarrow}</code>    | <code>{Rel}{MSA}{11}</code> |
| 782 | <code>\DeclareFlexSymbol{\leftleftarrows}</code>      | <code>{Rel}{MSA}{12}</code> |
| 783 | <code>\DeclareFlexSymbol{\rightrightarrows}</code>    | <code>{Rel}{MSA}{13}</code> |
| 784 | <code>\DeclareFlexSymbol{\upuparrows}</code>          | <code>{Rel}{MSA}{14}</code> |
| 785 | <code>\DeclareFlexSymbol{\downdownarrows}</code>      | <code>{Rel}{MSA}{15}</code> |
| 786 | <code>\DeclareFlexSymbol{\upharpoonright}</code>      | <code>{Rel}{MSA}{16}</code> |
| 787 | <code>\let\restriction\upharpoonright</code>          |                             |
| 788 | <code>\DeclareFlexSymbol{\downharpoonright}</code>    | <code>{Rel}{MSA}{17}</code> |
| 789 | <code>\DeclareFlexSymbol{\upharpoonleft}</code>       | <code>{Rel}{MSA}{18}</code> |
| 790 | <code>\DeclareFlexSymbol{\downharpoonleft}</code>     | <code>{Rel}{MSA}{19}</code> |
| 791 | <code>\DeclareFlexSymbol{\rightarrowtail}</code>      | <code>{Rel}{MSA}{1A}</code> |
| 792 | <code>\DeclareFlexSymbol{\leftarrowtail}</code>       | <code>{Rel}{MSA}{1B}</code> |
| 793 | <code>\DeclareFlexSymbol{\leftrightarrows}</code>     | <code>{Rel}{MSA}{1C}</code> |
| 794 | <code>\DeclareFlexSymbol{\rightleftarrows}</code>     | <code>{Rel}{MSA}{1D}</code> |
| 795 | <code>\DeclareFlexSymbol{\Lsh}</code>                 | <code>{Rel}{MSA}{1E}</code> |
| 796 | <code>\DeclareFlexSymbol{\Rsh}</code>                 | <code>{Rel}{MSA}{1F}</code> |
| 797 | <code>\DeclareFlexSymbol{\rightsquigarrow}</code>     | <code>{Rel}{MSA}{20}</code> |
| 798 | <code>\DeclareFlexSymbol{\leftrightsquigarrow}</code> | <code>{Rel}{MSA}{21}</code> |
| 799 | <code>\DeclareFlexSymbol{\looparrowleft}</code>       | <code>{Rel}{MSA}{22}</code> |
| 800 | <code>\DeclareFlexSymbol{\looparrowright}</code>      | <code>{Rel}{MSA}{23}</code> |
| 801 | <code>\DeclareFlexSymbol{\circeq}</code>              | <code>{Rel}{MSA}{24}</code> |
| 802 | <code>\DeclareFlexSymbol{\succsim}</code>             | <code>{Rel}{MSA}{25}</code> |
| 803 | <code>\DeclareFlexSymbol{\gtrsim}</code>              | <code>{Rel}{MSA}{26}</code> |
| 804 | <code>\DeclareFlexSymbol{\gtrapprox}</code>           | <code>{Rel}{MSA}{27}</code> |
| 805 | <code>\DeclareFlexSymbol{\multimap}</code>            | <code>{Rel}{MSA}{28}</code> |
| 806 | <code>\DeclareFlexSymbol{\therefore}</code>           | <code>{Rel}{MSA}{29}</code> |
| 807 | <code>\DeclareFlexSymbol{\because}</code>             | <code>{Rel}{MSA}{2A}</code> |
| 808 | <code>\DeclareFlexSymbol{\doteqdot}</code>            | <code>{Rel}{MSA}{2B}</code> |
| 809 | <code>\let\Doteq\doteqdot</code>                      |                             |
| 810 | <code>\DeclareFlexSymbol{\triangleq}</code>           | <code>{Rel}{MSA}{2C}</code> |
| 811 | <code>\DeclareFlexSymbol{\precsim}</code>             | <code>{Rel}{MSA}{2D}</code> |
| 812 | <code>\DeclareFlexSymbol{\lesssim}</code>             | <code>{Rel}{MSA}{2E}</code> |
| 813 | <code>\DeclareFlexSymbol{\lessapprox}</code>          | <code>{Rel}{MSA}{2F}</code> |
| 814 | <code>\DeclareFlexSymbol{\eqslantless}</code>         | <code>{Rel}{MSA}{30}</code> |
| 815 | <code>\DeclareFlexSymbol{\eqslantgtr}</code>          | <code>{Rel}{MSA}{31}</code> |
| 816 | <code>\DeclareFlexSymbol{\curlyeqprec}</code>         | <code>{Rel}{MSA}{32}</code> |
| 817 | <code>\DeclareFlexSymbol{\curlyeqsucc}</code>         | <code>{Rel}{MSA}{33}</code> |
| 818 | <code>\DeclareFlexSymbol{\preccurlyeq}</code>         | <code>{Rel}{MSA}{34}</code> |
| 819 | <code>\DeclareFlexSymbol{\leqq}</code>                | <code>{Rel}{MSA}{35}</code> |
| 820 | <code>\DeclareFlexSymbol{\leqslant}</code>            | <code>{Rel}{MSA}{36}</code> |
| 821 | <code>\DeclareFlexSymbol{\lessgtr}</code>             | <code>{Rel}{MSA}{37}</code> |
| 822 | <code>\DeclareFlexSymbol{\backprime}</code>           | <code>{Ord}{MSA}{38}</code> |
| 823 | <code>\DeclareFlexSymbol{\risingdotseq}</code>        | <code>{Rel}{MSA}{3A}</code> |
| 824 | <code>\DeclareFlexSymbol{\fallingdotseq}</code>       | <code>{Rel}{MSA}{3B}</code> |
| 825 | <code>\DeclareFlexSymbol{\succcurlyeq}</code>         | <code>{Rel}{MSA}{3C}</code> |

```

826 \DeclareFlexSymbol{\geqq}          {Rel}{MSA}{3D}
827 \DeclareFlexSymbol{\geqslant}      {Rel}{MSA}{3E}
828 \DeclareFlexSymbol{\gtrless}       {Rel}{MSA}{3F}

in amsfonts.sty

829 %% \DeclareFlexSymbol{\sqsubset}   {Rel}{MSA}{40}
830 %% \DeclareFlexSymbol{\sqsupset}   {Rel}{MSA}{41}
831 \DeclareFlexSymbol{\vartriangleright} {Rel}{MSA}{42}
832 \DeclareFlexSymbol{\vartriangleleft} {Rel}{MSA}{43}
833 \DeclareFlexSymbol{\trianglerighteq} {Rel}{MSA}{44}
834 \DeclareFlexSymbol{\trianglelefteq} {Rel}{MSA}{45}
835 \DeclareFlexSymbol{\bigstar}        {Ord}{MSA}{46}
836 \DeclareFlexSymbol{\between}       {Rel}{MSA}{47}
837 \DeclareFlexSymbol{\blacktriangledown} {Ord}{MSA}{48}
838 \DeclareFlexSymbol{\blacktriangleright} {Rel}{MSA}{49}
839 \DeclareFlexSymbol{\blacktriangleleft} {Rel}{MSA}{4A}
840 \DeclareFlexSymbol{\vartriangle}     {Rel}{MSA}{4D}
841 \DeclareFlexSymbol{\blacktriangle}   {Ord}{MSA}{4E}
842 \DeclareFlexSymbol{\triangledown}    {Ord}{MSA}{4F}
843 \DeclareFlexSymbol{\eqcirc}         {Rel}{MSA}{50}
844 \DeclareFlexSymbol{\lesseqgtr}     {Rel}{MSA}{51}
845 \DeclareFlexSymbol{\gtreqless}     {Rel}{MSA}{52}
846 \DeclareFlexSymbol{\lesseqqgtr}    {Rel}{MSA}{53}
847 \DeclareFlexSymbol{\gtreqqless}    {Rel}{MSA}{54}
848 \DeclareFlexSymbol{\Rrightarrow}    {Rel}{MSA}{56}
849 \DeclareFlexSymbol{\Lleftarrow}     {Rel}{MSA}{57}
850 \DeclareFlexSymbol{\veebar}         {Bin}{MSA}{59}
851 \DeclareFlexSymbol{\barwedge}       {Bin}{MSA}{5A}
852 \DeclareFlexSymbol{\doublebarwedge} {Bin}{MSA}{5B}

In amsfonts.sty

853 %% \DeclareFlexSymbol{\angle}      {Ord}{MSA}{5C}
854 \DeclareFlexSymbol{\measuredangle} {Ord}{MSA}{5D}
855 \DeclareFlexSymbol{\sphericalangle} {Ord}{MSA}{5E}
856 \DeclareFlexSymbol{\varpropto}     {Rel}{MSA}{5F}
857 \DeclareFlexSymbol{\smallsmile}    {Rel}{MSA}{60}
858 \DeclareFlexSymbol{\smallfrown}    {Rel}{MSA}{61}
859 \DeclareFlexSymbol{\Subset}        {Rel}{MSA}{62}
860 \DeclareFlexSymbol{\Supset}        {Rel}{MSA}{63}
861 \DeclareFlexSymbol{\Cup}           {Bin}{MSA}{64}
862 \let\doublecup\Cup
863 \DeclareFlexSymbol{\Cap}           {Bin}{MSA}{65}
864 \let\doublecap\Cap
865 \DeclareFlexSymbol{\curlywedge}    {Bin}{MSA}{66}
866 \DeclareFlexSymbol{\curlyvee}     {Bin}{MSA}{67}
867 \DeclareFlexSymbol{\leftthreetimes} {Bin}{MSA}{68}
868 \DeclareFlexSymbol{\rightthreetimes} {Bin}{MSA}{69}
869 \DeclareFlexSymbol{\subseteqq}     {Rel}{MSA}{6A}
870 \DeclareFlexSymbol{\supseteqq}     {Rel}{MSA}{6B}
871 \DeclareFlexSymbol{\bumpeq}        {Rel}{MSA}{6C}
872 \DeclareFlexSymbol{\Bumpeq}        {Rel}{MSA}{6D}

```



|                                       |                |
|---------------------------------------|----------------|
| 873 \DeclareFlexSymbol{\l11}          | {Rel}{MSA}{6E} |
| 874 \let\l1less\l11                   |                |
| 875 \DeclareFlexSymbol{\ggg}          | {Rel}{MSA}{6F} |
| 876 \let\gggtr\ggg                    |                |
| 877 \DeclareFlexSymbol{\circledS}     | {Ord}{MSA}{73} |
| 878 \DeclareFlexSymbol{\pitchfork}    | {Rel}{MSA}{74} |
| 879 \DeclareFlexSymbol{\dotplus}      | {Bin}{MSA}{75} |
| 880 \DeclareFlexSymbol{\backsim}      | {Rel}{MSA}{76} |
| 881 \DeclareFlexSymbol{\backsimeq}    | {Rel}{MSA}{77} |
| 882 \DeclareFlexSymbol{\complement}   | {Ord}{MSA}{7B} |
| 883 \DeclareFlexSymbol{\intercal}     | {Bin}{MSA}{7C} |
| 884 \DeclareFlexSymbol{\circledcirc}  | {Bin}{MSA}{7D} |
| 885 \DeclareFlexSymbol{\circledast}   | {Bin}{MSA}{7E} |
| 886 \DeclareFlexSymbol{\circleddash}  | {Bin}{MSA}{7F} |
| Begin AMSb declarations               |                |
| 887 \DeclareFlexSymbol{\lvertneqq}    | {Rel}{MSB}{00} |
| 888 \DeclareFlexSymbol{\gvertneqq}    | {Rel}{MSB}{01} |
| 889 \DeclareFlexSymbol{\nleq}         | {Rel}{MSB}{02} |
| 890 \DeclareFlexSymbol{\ngeq}         | {Rel}{MSB}{03} |
| 891 \DeclareFlexSymbol{\nless}        | {Rel}{MSB}{04} |
| 892 \DeclareFlexSymbol{\ngtr}         | {Rel}{MSB}{05} |
| 893 \DeclareFlexSymbol{\nprec}        | {Rel}{MSB}{06} |
| 894 \DeclareFlexSymbol{\nsucc}        | {Rel}{MSB}{07} |
| 895 \DeclareFlexSymbol{\lneqq}        | {Rel}{MSB}{08} |
| 896 \DeclareFlexSymbol{\gneqq}        | {Rel}{MSB}{09} |
| 897 \DeclareFlexSymbol{\nleqslant}    | {Rel}{MSB}{0A} |
| 898 \DeclareFlexSymbol{\ngeqslant}    | {Rel}{MSB}{0B} |
| 899 \DeclareFlexSymbol{\lneq}         | {Rel}{MSB}{0C} |
| 900 \DeclareFlexSymbol{\gneq}         | {Rel}{MSB}{0D} |
| 901 \DeclareFlexSymbol{\npreceq}      | {Rel}{MSB}{0E} |
| 902 \DeclareFlexSymbol{\nsucceq}      | {Rel}{MSB}{0F} |
| 903 \DeclareFlexSymbol{\precnsim}     | {Rel}{MSB}{10} |
| 904 \DeclareFlexSymbol{\succnsim}     | {Rel}{MSB}{11} |
| 905 \DeclareFlexSymbol{\lnsim}        | {Rel}{MSB}{12} |
| 906 \DeclareFlexSymbol{\gnsim}        | {Rel}{MSB}{13} |
| 907 \DeclareFlexSymbol{\nleqq}        | {Rel}{MSB}{14} |
| 908 \DeclareFlexSymbol{\ngeqq}        | {Rel}{MSB}{15} |
| 909 \DeclareFlexSymbol{\precneqq}     | {Rel}{MSB}{16} |
| 910 \DeclareFlexSymbol{\succneqq}     | {Rel}{MSB}{17} |
| 911 \DeclareFlexSymbol{\precnapprox}  | {Rel}{MSB}{18} |
| 912 \DeclareFlexSymbol{\succnapprox}  | {Rel}{MSB}{19} |
| 913 \DeclareFlexSymbol{\lnapprox}     | {Rel}{MSB}{1A} |
| 914 \DeclareFlexSymbol{\gnapprox}     | {Rel}{MSB}{1B} |
| 915 \DeclareFlexSymbol{\nsim}         | {Rel}{MSB}{1C} |
| 916 \DeclareFlexSymbol{\ncong}        | {Rel}{MSB}{1D} |
| 917 \DeclareFlexSymbol{\diagup}       | {Ord}{MSB}{1E} |
| 918 \DeclareFlexSymbol{\diagdown}     | {Ord}{MSB}{1F} |
| 919 \DeclareFlexSymbol{\varsubsetneq} | {Rel}{MSB}{20} |
| 920 \DeclareFlexSymbol{\varsupsetneq} | {Rel}{MSB}{21} |

|     |   |                             |
|-----|---|-----------------------------|
| 921 | <code>\DeclareFlexSymbol{\nsubseteqq}</code>          | <code>{Rel}{MSB}{22}</code> |
| 922 | <code>\DeclareFlexSymbol{\nsupseteqq}</code>          | <code>{Rel}{MSB}{23}</code> |
| 923 | <code>\DeclareFlexSymbol{\subsetneqq}</code>          | <code>{Rel}{MSB}{24}</code> |
| 924 | <code>\DeclareFlexSymbol{\supsetneqq}</code>          | <code>{Rel}{MSB}{25}</code> |
| 925 | <code>\DeclareFlexSymbol{\varsubsetneqq}</code>       | <code>{Rel}{MSB}{26}</code> |
| 926 | <code>\DeclareFlexSymbol{\varsupsetneqq}</code>       | <code>{Rel}{MSB}{27}</code> |
| 927 | <code>\DeclareFlexSymbol{\subsetneq}</code>           | <code>{Rel}{MSB}{28}</code> |
| 928 | <code>\DeclareFlexSymbol{\supsetneq}</code>           | <code>{Rel}{MSB}{29}</code> |
| 929 | <code>\DeclareFlexSymbol{\nsubseteq}</code>           | <code>{Rel}{MSB}{2A}</code> |
| 930 | <code>\DeclareFlexSymbol{\nsupseteq}</code>           | <code>{Rel}{MSB}{2B}</code> |
| 931 | <code>\DeclareFlexSymbol{\nparallel}</code>           | <code>{Rel}{MSB}{2C}</code> |
| 932 | <code>\DeclareFlexSymbol{\nmid}</code>                | <code>{Rel}{MSB}{2D}</code> |
| 933 | <code>\DeclareFlexSymbol{\nshortmid}</code>           | <code>{Rel}{MSB}{2E}</code> |
| 934 | <code>\DeclareFlexSymbol{\nshortparallel}</code>      | <code>{Rel}{MSB}{2F}</code> |
| 935 | <code>\DeclareFlexSymbol{\nvdash}</code>              | <code>{Rel}{MSB}{30}</code> |
| 936 | <code>\DeclareFlexSymbol{\nVdash}</code>              | <code>{Rel}{MSB}{31}</code> |
| 937 | <code>\DeclareFlexSymbol{\nvDash}</code>              | <code>{Rel}{MSB}{32}</code> |
| 938 | <code>\DeclareFlexSymbol{\nVDash}</code>              | <code>{Rel}{MSB}{33}</code> |
| 939 | <code>\DeclareFlexSymbol{\ntrianglerighteq}</code>    | <code>{Rel}{MSB}{34}</code> |
| 940 | <code>\DeclareFlexSymbol{\ntrianglelefteq}</code>     | <code>{Rel}{MSB}{35}</code> |
| 941 | <code>\DeclareFlexSymbol{\ntriangleleft}</code>       | <code>{Rel}{MSB}{36}</code> |
| 942 | <code>\DeclareFlexSymbol{\ntriangleright}</code>      | <code>{Rel}{MSB}{37}</code> |
| 943 | <code>\DeclareFlexSymbol{\nleftarrow}</code>          | <code>{Rel}{MSB}{38}</code> |
| 944 | <code>\DeclareFlexSymbol{\nrightarrow}</code>         | <code>{Rel}{MSB}{39}</code> |
| 945 | <code>\DeclareFlexSymbol{\nLeftarrow}</code>          | <code>{Rel}{MSB}{3A}</code> |
| 946 | <code>\DeclareFlexSymbol{\nRightarrow}</code>         | <code>{Rel}{MSB}{3B}</code> |
| 947 | <code>\DeclareFlexSymbol{\nLeftrightarrow}</code>     | <code>{Rel}{MSB}{3C}</code> |
| 948 | <code>\DeclareFlexSymbol{\nleqtrightharpoonup}</code> | <code>{Rel}{MSB}{3D}</code> |
| 949 | <code>\DeclareFlexSymbol{\divideontimes}</code>       | <code>{Bin}{MSB}{3E}</code> |
| 950 | <code>\DeclareFlexSymbol{\varnothing}</code>          | <code>{Ord}{MSB}{3F}</code> |
| 951 | <code>\DeclareFlexSymbol{\nexists}</code>             | <code>{Ord}{MSB}{40}</code> |
| 952 | <code>\DeclareFlexSymbol{\Finv}</code>                | <code>{Ord}{MSB}{60}</code> |
| 953 | <code>\DeclareFlexSymbol{\Game}</code>                | <code>{Ord}{MSB}{61}</code> |

In amsfonts.sty:

|     |   |                             |
|-----|---|-----------------------------|
| 954 | <code>%\DeclareFlexSymbol{\mho}</code>          | <code>{Ord}{MSB}{66}</code> |
| 955 | <code>\DeclareFlexSymbol{\eth}</code>           | <code>{Ord}{MSB}{67}</code> |
| 956 | <code>\DeclareFlexSymbol{\eqsim}</code>         | <code>{Rel}{MSB}{68}</code> |
| 957 | <code>\DeclareFlexSymbol{\beth}</code>          | <code>{Ord}{MSB}{69}</code> |
| 958 | <code>\DeclareFlexSymbol{\gimel}</code>         | <code>{Ord}{MSB}{6A}</code> |
| 959 | <code>\DeclareFlexSymbol{\daleth}</code>        | <code>{Ord}{MSB}{6B}</code> |
| 960 | <code>\DeclareFlexSymbol{\lessdot}</code>       | <code>{Bin}{MSB}{6C}</code> |
| 961 | <code>\DeclareFlexSymbol{\gtrdot}</code>        | <code>{Bin}{MSB}{6D}</code> |
| 962 | <code>\DeclareFlexSymbol{\ltimes}</code>        | <code>{Bin}{MSB}{6E}</code> |
| 963 | <code>\DeclareFlexSymbol{\rtimes}</code>        | <code>{Bin}{MSB}{6F}</code> |
| 964 | <code>\DeclareFlexSymbol{\shortmid}</code>      | <code>{Rel}{MSB}{70}</code> |
| 965 | <code>\DeclareFlexSymbol{\shortparallel}</code> | <code>{Rel}{MSB}{71}</code> |
| 966 | <code>\DeclareFlexSymbol{\smallsetminus}</code> | <code>{Bin}{MSB}{72}</code> |
| 967 | <code>\DeclareFlexSymbol{\thicksim}</code>      | <code>{Rel}{MSB}{73}</code> |
| 968 | <code>\DeclareFlexSymbol{\thickapprox}</code>   | <code>{Rel}{MSB}{74}</code> |

```

969 \DeclareFlexSymbol{\approxeq}      {Rel}{MSB}{75}
970 \DeclareFlexSymbol{\succapprox}    {Rel}{MSB}{76}
971 \DeclareFlexSymbol{\precapprox}    {Rel}{MSB}{77}
972 \DeclareFlexSymbol{\curvearrowleft} {Rel}{MSB}{78}
973 \DeclareFlexSymbol{\curvearrowright}{Rel}{MSB}{79}
974 \DeclareFlexSymbol{\digamma}       {Ord}{MSB}{7A}
975 \DeclareFlexSymbol{\varkappa}      {Ord}{MSB}{7B}
976 \DeclareFlexSymbol{\Bbbk}         {Ord}{MSB}{7C}
977 \DeclareFlexSymbol{\hslash}        {Ord}{MSB}{7D}

```

In amsfonts.sty:

```

978 %\DeclareFlexSymbol{\hbar}         {Ord}{MSB}{7E}
979 \DeclareFlexSymbol{\backepsilon}    {Rel}{MSB}{7F}
980 \ExplSyntaxOff
981 \</msabm>

```

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| Symbols                                   |   |
|---|---|
| \   | \@symDeB ..... 92                       |
| "   | \@symDeL ..... 90                       |
| '   | \@symDeR ..... 91                       |
| *   | \@symErr ..... 313                      |
| -   | \@symOrd ..... 83                       |
| .   | \@symPun ..... 87                       |
| /   | \@symRel ..... 86                       |
| :   | \@symVar ..... 84, 96–98                |
| =   | \@symextension ..... 332, 335           |
| \@begindocumenthook                       | \@syntype . 83–93, 96–98, 100, 265, 344 |
| \@firstofone                              | \@syntype@ord ..... 344, 346            |
| \@gobble                                  | \@tempb ..... 228, 233, 237, 334, 335   |
| \@gobblethree                             | \@typeset@protect ..... 16              |
| \@height                                  | \@vereq ..... 722                       |
| \@ifpackageloaded                         | \_ ..... 35, 38, 41, 44, 349            |
| \@ifpackagewith                           | \l ..... 404                            |
| \@ifundefined                             |   |
| \@nil                                     |   |
| \@onefilewithoptions                      | <b>A</b>                                |
| \@sym 13, 15, 94, 229, 255, 264, 329, 344 | \active ..... 225, 260                  |
| \@sym@ord ..... 344, 347                  | \aleph ..... 572                        |
| \@sym@ord@a ..... 347, 350                | \alpha ..... 467                        |
| \@symAcc ..... 94                         | \amalg ..... 601                        |
| \@symBin ..... 85                         | \angle ..... 712, 853                   |
| \@symCoi ..... 88                         | \approx ..... 637                       |
| \@symCUs ..... 89                         | \approxeq ..... 969                     |
| \@symDeA ..... 93                         | \Arrowvert ..... 700                    |
|   | \arrowvert ..... 699                    |

|                                     |          |                               |     |
|-------------------------------------|----------|-------------------------------|-----|
| <code>\ast</code> .....             | 569, 617 | <code>\bracevert</code> ..... | 698 |
| <code>\asymp</code> .....           | 655      | <code>\buildrel</code> .....  | 728 |
| <code>\AtBeginDocument</code> ..... | 371      | <code>\bullet</code> .....    | 603 |
| <code>\AtEndOfPackage</code> .....  | 6        | <code>\Bumpeq</code> .....    | 872 |
|                                     |          | <code>\bumpeq</code> .....    | 871 |

## B

|  |                                   |
|--|-----------------------------------|
| <code>\backepsilon</code> .....        | 979                               |
| <code>\backprime</code> .....          | 822                               |
| <code>\backsim</code> .....            | 880                               |
| <code>\backsimeq</code> .....          | 881                               |
| <code>\backslash</code> .....          | 707                               |
| <code>\barwedge</code> .....           | 851                               |
| <code>\baselineskip</code> .....       | 745                               |
| <code>\Bbbk</code> .....               | 976                               |
| <code>\because</code> .....            | 807                               |
| <code>\begingroup</code> .....         | 227, 254, 261, 342, 348, 362, 752 |
| <code>\beta</code> .....               | 468                               |
| <code>\beth</code> .....               | 957                               |
| <code>\between</code> .....            | 836                               |
| <code>\bigcap</code> .....             | 664                               |
| <code>\bigcirc</code> .....            | 614                               |
| <code>\bigcup</code> .....             | 665                               |
| <code>\bigodot</code> .....            | 671                               |
| <code>\bigoplus</code> .....           | 670                               |
| <code>\bigotimes</code> .....          | 669                               |
| <code>\bigsqcup</code> .....           | 673                               |
| <code>\bigstar</code> .....            | 835                               |
| <code>\bigtriangledown</code> .....    | 591                               |
| <code>\bigtriangleup</code> .....      | 590                               |
| <code>\biguplus</code> .....           | 663                               |
| <code>\bigvee</code> .....             | 661                               |
| <code>\bigwedge</code> .....           | 662                               |
| <code>\binrel@</code> .....            | 326                               |
| <code>\binrel@@</code> .....           | 305, 318–324                      |
| <code>\binrel@a</code> .....           | 317, 329                          |
| <code>\binrel@sym</code> .....         | 304, 329                          |
| <code>\blacklozenge</code> .....       | 771                               |
| <code>\blacksquare</code> .....        | 768                               |
| <code>\blacktriangle</code> .....      | 841                               |
| <code>\blacktriangledown</code> .....  | 837                               |
| <code>\blacktriangleleft</code> .....  | 839                               |
| <code>\blacktriangleright</code> ..... | 838                               |
| <code>\bot</code> .....                | 580                               |
| <code>\bowtie</code> .....             | 731                               |
| <code>\boxdot</code> .....             | 293, 298, 301                     |
| <code>\boxdot</code> .....             | 764                               |
| <code>\boxminus</code> .....           | 776                               |
| <code>\boxplus</code> .....            | 765                               |
| <code>\boxtimes</code> .....           | 766                               |

## C

|                                      |   |
|--------------------------------------|---|
| <code>\c@ncel</code> .....           | 726   |
| <code>\Cap</code> .....              | 863, 864  |
| <code>\cap</code> .....              | 594   |
| <code>\catcode</code> ....           | 7, 12, 224, 225, 259, 260   |
| <code>\cdot</code> .....             | 616   |
| <code>\cdotOrd</code> .....          | 658, 659  |
| <code>\cdottp</code> .....           | 659, 743  |
| <code>\cdots</code> .....            | 743   |
| <code>\centerdot</code> .....        | 769   |
| <code>\char</code> .....             | 257   |
| <code>\check@mathfonts</code> .....  | 262   |
| <code>\chi</code> .....              | 487   |
| <code>\circ</code> .....             | 613   |
| <code>\circeq</code> .....           | 801   |
| <code>\circlearrowleft</code> .....  | 773   |
| <code>\circlearrowright</code> ..... | 772   |
| <code>\circledast</code> .....       | 885   |
| <code>\circledcirc</code> .....      | 884   |
| <code>\circleddash</code> .....      | 886   |
| <code>\circledS</code> .....         | 877   |
| <code>\cleaders</code> .....         | 292, 296, 300   |
| <code>\clist</code> .....            | 334   |
| <code>\clubsuit</code> .....         | 585   |
| <code>\colon</code> .....            | 437   |
| <code>\complement</code> .....       | 882   |
| <code>\cong</code> .....             | 722   |
| <code>\coprod</code> .....           | 660   |
| <code>\copy</code> .....             | 292, 297  |
| <code>\crr</code> .....              | 714, 715, 717   |
| <code>\cs</code> .....               | 34, 37, 40, 43, 50–62,<br>64, 67, 68, 71, 74, 78, 79, 83–<br>94, 96–98, 102–114, 116–143,<br>145–160, 162–189, 192, 194–<br>221, 228, 242, 244, 255, 263–<br>267, 270, 358, 412–422, 424,<br>426, 429, 431–433, 659, 762, 763 |
| <code>\csname</code> .....           | 248   |
| <code>\Cup</code> .....              | 861, 862  |
| <code>\cup</code> .....              | 595   |
| <code>\curlyeqprec</code> .....      | 816   |
| <code>\curlyeqsucc</code> .....      | 817   |
| <code>\curlyvee</code> .....         | 866   |
| <code>\curlywedge</code> .....       | 865   |

|   |          |   |                  |
|---|----------|---|------------------|
| <code>\curvearrowleft</code> .....                  | 972      |   |                  |
| <code>\curvearrowright</code> .....                 | 973      |   |                  |
| <b>D</b>  |          | <b>E</b>  |                  |
| <code>\dagger</code> .....                          | 597      | <code>\edef</code> .....                                | 5, 224, 259, 755 |
| <code>\daleth</code> .....                          | 959      | <code>\ell</code> .....                                 | 498              |
| <code>\dashv</code> .....                           | 624      | <code>\else</code> 16, 234, 273, 307–313, 354, 377, 379 |                  |
| <code>\ddagger</code> .....                         | 596      | <code>\emptyset</code> .....                            | 577              |
| <code>\ddots</code> .....                           | 747      | <code>\endcsname</code> .....                           | 248              |
| <code>\DeclareFlexCompoundSymbol</code> .....       |          | <code>\endgroup</code> .....                            |                  |
| ..... 247, 709, 711, 712,                           |          | 239, 257, 277, 342, 349, 369, 753                       |                  |
| 720–722, 726–739, 743, 744, 747                     |          | <code>\endinput</code> .....                            | 406              |
| <code>\DeclareFlexDelimiter</code> .. 242, 674–707  |          | <code>\epsilon</code> .....                             | 471              |
| <code>\DeclareFlexSymbol</code> . 226, 243, 434–    |          | <code>\eqcirc</code> .....                              | 843              |
| 565, 567–658, 660–673, 708,                         |          | <code>\eqsim</code> .....                               | 956              |
| 710, 764–786, 788–808, 810–                         |          | <code>\eqslantgtr</code> .....                          | 815              |
| 861, 863, 865–873, 875, 877–979                     |          | <code>\eqslantless</code> .....                         | 814              |
| <code>\DeclareOption</code> ..... 14, 388, 390–392  |          | <code>\equiv</code> .....                               | 654              |
| <code>\DeclareRobustCommand</code> .....            |          | <code>\eta</code> .....                                 | 473              |
| ..... 248, 251, 252, 281, 340, 341                  |          | <code>\eth</code> .....                                 | 955              |
| <code>\def</code> .. 15, 19–33, 226, 247, 253, 261, |          | <code>\everymath</code> .....                           | 268              |
| 269, 285, 291, 295, 299, 304,                       |          | <code>\ExecuteOptions</code> .....                      | 393              |
| 317–324, 326, 332, 344, 346,                        |          | <code>\exists</code> .....                              | 583              |
| 347, 350, 363, 372, 566, 752, 754                   |          | <code>\exp</code> 16, 65, 69, 75, 76, 229, 230, 232,    |                  |
| <code>\Delta</code> .....                           | 442      | 244, 248, 313, 314, 335, 347, 418                       |                  |
| <code>\delta</code> .....                           | 470      | <code>\expandafter</code> .....                         | 274, 368         |
| <code>\diagdown</code> .....                        | 918      | <code>\ExplSyntaxOff</code> .....                       | 756, 980         |
| <code>\diagup</code> .....                          | 917      | <code>\ExplSyntaxOn</code> .....                        | 411, 760         |
| <code>\diamond</code> .....                         | 602      | <b>F</b>  |                  |
| <code>\diamondsuit</code> .....                     | 586      | <code>\fallingdotseq</code> .....                       | 824              |
| <code>\digamma</code> .....                         | 974      | <code>\fi</code> ... 16, 238, 276, 313, 356, 381, 382   |                  |
| <code>\displaylimits</code> .....                   | 47, 49   | <code>\Finv</code> .....                                | 952              |
| <code>\div</code> .....                             | 605      | <code>\flat</code> .....                                | 501              |
| <code>\divideontimes</code> .....                   | 949      | <code>\flexi@stop</code> .....                          | 364, 368         |
| <code>\do</code> .....                              | 5, 11    | <code>\forall</code> .....                              | 582              |
| <code>\Doteq</code> .....                           | 809      | <code>\frown</code> .....                               | 508              |
| <code>\doteq</code> .....                           | 728      | <b>G</b>  |                  |
| <code>\doteqdot</code> .....                        | 808, 809 | <code>\Game</code> .....                                | 953              |
| <code>\dotplus</code> .....                         | 879      | <code>\Gamma</code> .....                               | 441              |
| <code>\doublebarwedge</code> .....                  | 852      | <code>\gamma</code> .....                               | 469              |
| <code>\doublecap</code> .....                       | 864      | <code>\gdef</code> .....                                | 318–324          |
| <code>\doublecup</code> .....                       | 862      | <code>\ge</code> .....                                  | 399              |
| <code>\Downarrow</code> .....                       | 705      | <code>\geq</code> .....                                 | 399, 634         |
| <code>\downarrow</code> .....                       | 702      | <code>\geqq</code> .....                                | 826              |
| <code>\downdownarrows</code> .....                  | 785      | <code>\geqslant</code> .....                            | 827              |
| <code>\downharpoonleft</code> .....                 | 790      | <code>\gets</code> .....                                | 402              |
| <code>\downharpoonright</code> .....                | 788      | <code>\gg</code> .....                                  | 646              |
| <code>\dp</code> .....                              | 287      | <code>\ggg</code> .....                                 | 875, 876         |
|   |          | <code>\gggtr</code> .....                               | 876              |
|   |          | <code>\gimel</code> .....                               | 958              |
|   |          | <code>\global</code> .....                              | 101              |

|                             |                                   |                                  |                                   |
|-----------------------------|-----------------------------------|----------------------------------|-----------------------------------|
| $\backslash$ gnapprox       | 914                               | $\backslash$ kern                | 746, 749                          |
| $\backslash$ gneq           | 900                               |                                  |                                   |
| $\backslash$ gneqq          | 896                               |                                  |                                   |
| $\backslash$ gnsim          | 906                               | <b>L</b>                         |                                   |
| $\backslash$ gtrapprox      | 804                               | $\backslash$ Lambda              | 444                               |
| $\backslash$ gtrdot         | 961                               | $\backslash$ lambda              | 477                               |
| $\backslash$ gtreqless      | 845                               | $\backslash$ land                | 396                               |
| $\backslash$ gtreqqless     | 847                               | $\backslash$ langle              | 675                               |
| $\backslash$ gtrless        | 828                               | $\backslash$ lbrace              | 677                               |
| $\backslash$ gtrsim         | 803                               | $\backslash$ lccode              | 236, 274, 349                     |
| $\backslash$ gvertneqq      | 888                               | $\backslash$ lceil               | 679                               |
|                             |                                   | $\backslash$ ldotp               | 566                               |
|                             |                                   | $\backslash$ ldotPun             | 565, 566                          |
| <b>H</b>                    |                                   | $\backslash$ le                  | 398                               |
| $\backslash$ hbar           | 709, 978                          | $\backslash$ leaders             | 717                               |
| $\backslash$ hbarOrd        | 708, 709                          | $\backslash$ leavevmode          | 281                               |
| $\backslash$ hbox           | 282, 286,                         | $\backslash$ Leftarrow           | 631, 735, 739                     |
|                             | 293, 297, 301, 327, 746, 749, 750 | $\backslash$ leftarrow           |                                   |
| $\backslash$ heartsuit      | 587                               |                                  | 296, 300, 402, 649, 730, 736, 738 |
| $\backslash$ hexnumber@     | 412–415, 426, 755, 762, 763       | $\backslash$ leftarrowfill@      | 295                               |
| $\backslash$ hfill          | 293, 297, 301, 717                | $\backslash$ leftarrowtail       | 792                               |
| $\backslash$ hookleftarrow  | 730                               | $\backslash$ leftharpoondown     | 510                               |
| $\backslash$ hookrightarrow | 729                               | $\backslash$ leftharpoonup       | 509                               |
| $\backslash$ hrule          | 717                               | $\backslash$ leftleftarrows      | 782                               |
| $\backslash$ hslash         | 977                               | $\backslash$ Leftrightarrow      | 630                               |
| $\backslash$ ht             | 287, 291, 295, 299                | $\backslash$ leftrightarrow      | 648                               |
|                             |                                   | $\backslash$ leftrightarrowfill@ | 299                               |
| <b>I</b>                    |                                   | $\backslash$ leftrightarrows     | 793                               |
| $\backslash$ ialign         | 713                               | $\backslash$ leftrightharpoons   | 775                               |
| $\backslash$ if             | 351                               | $\backslash$ leftrightsquigarrow | 798                               |
| $\backslash$ ifcat          | 232, 271                          | $\backslash$ leftthreetimes      | 867                               |
| $\backslash$ iff            | 740                               | $\backslash$ leq                 | 398, 633                          |
| $\backslash$ ifmmode        | 267                               | $\backslash$ leqq                | 819                               |
| $\backslash$ ifnum          | 376, 378                          | $\backslash$ leqslant            | 820                               |
| $\backslash$ iftrue         | 267                               | $\backslash$ lessapprox          | 813                               |
| $\backslash$ ifx            | 16, 306–312                       | $\backslash$ lessdot             | 960                               |
| $\backslash$ Im             | 574                               | $\backslash$ lesseqgtr           | 844                               |
| $\backslash$ imath          | 496                               | $\backslash$ lesseqqgtr          | 846                               |
| $\backslash$ in             | 644, 726                          | $\backslash$ lessgtr             | 821                               |
| $\backslash$ infty          | 575                               | $\backslash$ lesssim             | 812                               |
| $\backslash$ int            | 666                               | $\backslash$ let                 | 11, 13, 47–49, 100, 101,          |
| $\backslash$ intercal       | 883                               |                                  | 233, 237, 249, 328, 329, 344,     |
| $\backslash$ intlimits      | 48, 56, 88                        |                                  | 345, 787, 809, 862, 864, 874, 876 |
| $\backslash$ iota           | 475                               | $\backslash$ lfloor              | 681                               |
|                             |                                   | $\backslash$ lggroup             | 696                               |
| <b>J</b>                    |                                   | $\backslash$ hookRel             | 567, 729                          |
| $\backslash$ jmath          | 497                               | $\backslash$ lineskiplimit       | 745                               |
| $\backslash$ joinord        | 723–725, 729–736, 738, 739        | $\backslash$ ll                  | 647                               |
|                             |                                   | $\backslash$ Lleftarrow          | 849                               |
| <b>K</b>                    |                                   | $\backslash$ lll                 | 873, 874                          |
| $\backslash$ kappa          | 476                               | $\backslash$ llless              | 874                               |

|   |  |                                     |  |
|---|--|-------------------------------------|--|
| <code>\lmoustache</code> .....          | 694  | <code>\mathchars@reset</code> ..... | 342, 344   |
| <code>\lnapprox</code> .....            | 913  | <code>\mathchoice</code> .....      | 328  |
| <code>\lneq</code> .....                | 899  | <code>\mathclose</code> .....       | 91, 97   |
| <code>\lneqq</code> .....               | 895  | <code>\mathcode</code> .....        | 235, 363,<br>364, 373–376, 378, 380, 383–385                                 |
| <code>\lnot</code> .....                | 395  | <code>\mathinner</code> .....       | 98   |
| <code>\lnsim</code> .....               | 905  | <code>\mathop</code> .....          | 88, 89, 711  |
| <code>\long</code> .....                | 363  | <code>\mathopen</code> .....        | 90, 96   |
| <code>\Longleftarrow</code> .....       | 735  | <code>\mathord</code> .....         | 83, 84, 92   |
| <code>\longleftarrow</code> .....       | 736  | <code>\mathpalette</code> .....     | 722, 726, 727, 753   |
| <code>\Longleftrightharrow</code> ..... | 739, 741   | <code>\mathpunct</code> .....       | 87, 659  |
| <code>\longleftrightharrow</code> ..... | 738  | <code>\mathrel</code> .....         | 86, 93, 715  |
| <code>\longmapsto</code> .....          | 737  | <code>\mathsm@sh</code> .....       | 753  |
| <code>\Longrightarrow</code> .....      | 733  | <code>\Mathstrutbox@</code> .....   | 287  |
| <code>\longrightarrow</code> .....      | 734, 737   | <code>\measuredangle</code> .....   | 854  |
| <code>\looparrowleft</code> .....       | 799  | <code>\mg@acc</code> .....          | 24   |
| <code>\looparrowright</code> .....      | 800  | <code>\mg@arr</code> .....          | 23   |
| <code>\lor</code> .....                 | 397  | <code>\mg@Bbb</code> .....          | 30   |
| <code>\lowercase</code> .....           | 237, 275, 349  | <code>\mg@bflatin</code> .....      | 29   |
| <code>\lozenge</code> .....             | 770  | <code>\mg@bin</code> .....          | 19, 416, 431, 432  |
| <code>\Lsh</code> .....                 | 795  | <code>\mg@cal</code> .....          | 31   |
| <code>\ltimes</code> .....              | 962  | <code>\mg@cop</code> .....          | 25, 433  |
| <code>\lVert</code> .....               | 686  | <code>\mg@del</code> .....          | 22, 417, 433   |
| <code>\lvert</code> .....               | 688  | <code>\mg@digit</code> .....        | 33, 418, 422   |
| <code>\lvertneqq</code> .....           | 887  | <code>\mg@frac</code> .....         | 32   |
| <b>M</b>                                |  |                                     |  |
| <code>\m@Bin</code> .....               | 52, 53, 104, 105   | <code>\mg@Greek</code> .....        | 28, 422, 424, 429  |
| <code>\m@COi</code> .....               | 56, 108  | <code>\mg@greek</code> .....        | 27, 421  |
| <code>\m@COs</code> .....               | 55, 107  | <code>\mg@Latin</code> .....        | 420  |
| <code>\m@DeA</code> .....               | 60, 112  | <code>\mg@latin</code> .....        | 26, 419–421, 424, 429  |
| <code>\m@DeB</code> .....               | 59, 111  | <code>\mg@nre</code> .....          | 21   |
| <code>\m@DeL</code> .....               | 57, 109  | <code>\mg@OML</code> .....          | 419  |
| <code>\m@DeR</code> .....               | 58, 110  | <code>\mg@OMS</code> .....          | 416  |
| <code>\m@Ord</code> .....               | 50, 102  | <code>\mg@OMX</code> .....          | 417  |
| <code>\m@Pun</code> .....               | 54, 106  | <code>\mg@ord</code> .....          | 432  |
| <code>\m@Rad</code> .....               | 61, 113  | <code>\mg@rel</code> .....          | 20, 431  |
| <code>\m@th</code> .....                | 291, 295, 299, 714   | <code>\mho</code> .....             | 954  |
| <code>\m@Var</code> .....               | 51, 103  | <code>\mid</code> .....             | 623  |
| <code>\mapsto</code> .....              | 721  | <code>\mkern</code> .....           | 269, 270, 292–<br>294, 296–298, 300–302, 709,<br>715, 717, 724, 725, 748–750 |
| <code>\mapstochar</code> .....          | 737  | <code>\models</code> .....          | 732  |
| <code>\mapstoOrd</code> .....           | 657, 721   | <code>\mp</code> .....              | 611  |
| <code>\math</code> .....                | 34, 37, 40, 43,<br>50–62, 64, 65, 67–69, 71, 74, 75,<br>78, 83–94, 96–98, 102–114, 116–<br>143, 145–160, 162–189, 192,<br>194–221, 223, 306–312, 318–<br>324, 340, 352, 353, 355, 358, 359 | <code>\mskip</code> .....           | 270, 741   |
| <code>\mathbin</code> .....             | 85   | <code>\mu</code> .....              | 478  |
| <code>\mathchar</code> .....            | 753–755  | <code>\multimap</code> .....        | 805  |
| <code>\mathchardef</code> .....         | 363, 364, 380  | <code>\muskip</code> .....          | 269  |
| <b>N</b>                                |  |                                     |  |
| <code>\nabla</code> .....               | 578  |                                     |  |
| <code>\namelimits</code> .....          | 49   |                                     |  |





|   |  |                                    |                       |
|---|--|------------------------------------|-----------------------|
| <code>\ProvidesExplPackage</code> ..... | 3  | <code>\searrow</code> .....        | 627                   |
| <code>\ProvidesFile</code> .....        | 339  | <code>\setbox</code> .....         | 286, 327              |
| <code>\ProvidesSymbols</code> ..        | 339, 408–410, 759  | <code>\setboxz@h</code> .....      | 291, 295, 299         |
| <code>\Psi</code> .....                 | 450  | <code>\setminus</code> .....       | 615                   |
| <code>\psi</code> .....                 | 488  | <code>\sharp</code> .....          | 503                   |
| <b>R</b>                                |  |                                    |                       |
| <code>\raise</code> .....               | 282, 748, 750  | <code>\shortmid</code> .....       | 964                   |
| <code>\rangle</code> .....              | 674  | <code>\shortparallel</code> .....  | 965                   |
| <code>\rbrace</code> .....              | 676  | <code>\Sigma</code> .....          | 447                   |
| <code>\rceil</code> .....               | 678  | <code>\sigma</code> .....          | 483                   |
| <code>\Re</code> .....                  | 573  | <code>\sim</code> .....            | 651, 722              |
| <code>\relax</code> .....               | 8,<br>11, 232, 235, 236, 249, 271, 274,<br>345, 363, 364, 380, 385, 394, 761 | <code>\simeq</code> .....          | 652                   |
| <code>\Relbar</code> .....              | 733, 735, 754, 755   | <code>\smallfrown</code> .....     | 858                   |
| <code>\relbar</code> ..                 | 291, 295, 299, 734, 736, 752   | <code>\smallint</code> .....       | 589                   |
| <code>\renewcommand</code> ..           | 395–404, 724, 725, 740   | <code>\smallsetminus</code> .....  | 966                   |
| <code>\RequirePackage</code> .....      | 2, 405, 761  | <code>\smallsmile</code> .....     | 857                   |
| <code>\resetMathstrut@</code> .....     | 285  | <code>\smash@</code> .....         | 752                   |
| <code>\restriction</code> .....         | 787  | <code>\smile</code> .....          | 507                   |
| <code>\rfloor</code> .....              | 680  | <code>\space</code> .....          | 373–376, 378, 383–385 |
| <code>\rgroup</code> .....              | 697  | <code>\spadesuit</code> .....      | 588                   |
| <code>\rho</code> .....                 | 482  | <code>\sphericalangle</code> ..... | 855                   |
| <code>\rho hookRel</code> .....         | 568, 730   | <code>\sqcap</code> .....          | 598                   |
| <code>\rightarrow</code> .....          | 632, 733, 739  | <code>\sqcup</code> .....          | 599                   |
| <code>\rightarrow</code> .....          | 294,<br>302, 403, 650, 721, 729, 734, 738                                    | <code>\sqsubset</code> .....       | 829                   |
| <code>\rightarrowfill@</code> .....     | 291  | <code>\sqsubseteq</code> .....     | 620                   |
| <code>\rightarrowtail</code> .....      | 791  | <code>\sqsupset</code> .....       | 830                   |
| <code>\rightharpoondown</code> .....    | 512  | <code>\sqsupseteq</code> .....     | 621                   |
| <code>\rightharpoonup</code> .....      | 511  | <code>\square</code> .....         | 767                   |
| <code>\rightleftarrows</code> .....     | 794  | <code>\star</code> .....           | 506                   |
| <code>\rightleftharpoons</code> .....   | 727, 774   | <code>\std@equal</code> .....      | 364                   |
| <code>\rightrightarrows</code> .....    | 783  | <code>\std@minus</code> .....      | 363, 380              |
| <code>\rightsquigarrow</code> .....     | 797  | <code>\string</code> .....         | 274, 347, 755         |
| <code>\rightthreetimes</code> .....     | 868  | <code>\Subset</code> .....         | 859                   |
| <code>\risingdotseq</code> .....        | 823  | <code>\subset</code> .....         | 641                   |
| <code>\rlh@</code> .....                | 727  | <code>\subseteq</code> .....       | 643                   |
| <code>\rmoustache</code> .....          | 695  | <code>\subseteqeq</code> .....     | 869                   |
| <code>\Rrightarrow</code> .....         | 848  | <code>\subsetneq</code> .....      | 927                   |
| <code>\Rsh</code> .....                 | 796  | <code>\subsetneqq</code> .....     | 923                   |
| <code>\rtimes</code> .....              | 963  | <code>\succ</code> .....           | 635                   |
| <code>\rVert</code> .....               | 687  | <code>\succapprox</code> .....     | 970                   |
| <code>\rvert</code> .....               | 689  | <code>\succcurlyeq</code> .....    | 825                   |
| <b>S</b>                                |  |                                    |                       |
| <code>\scriptchar</code> .....          | 252  | <code>\succeq</code> .....         | 638                   |
| <code>\scriptfont</code> .....          | 252, 282   | <code>\succapprox</code> .....     | 912                   |
| <code>\scriptstyle</code> .....         | 714  | <code>\succneqq</code> .....       | 910                   |
|   |  | <code>\succnsim</code> .....       | 904                   |
|   |  | <code>\succsim</code> .....        | 802                   |
|   |  | <code>\sum</code> .....            | 668                   |
|   |  | <code>\sumlimits</code> .....      | 47, 55, 89            |
|   |  | <code>\Supset</code> .....         | 860                   |
|   |  | <code>\supset</code> .....         | 640                   |
|   |  | <code>\supseteq</code> .....       | 642                   |



|              |  |                                  |
|--------------|--|----------------------------------|
|              | <b>Z</b>   | 293, 295, 297–299, 301, 327, 745 |
| <b>\z@</b>   | 224, 225, 236, 259,<br>260, 269, 274, 286, 287, 291– |                                  |
| <b>\zeta</b> |  | 472                              |